



























Suggested Retail Prices (January 2020)

Power Conditioners		SRP	
PC-4 EVO+ Reference Model. 12 outputs. DC Blocker. Distribution bars - silvered OFC 45 QMM. Internal wiring - silvered OFHC 4 QMM. Hi-Flux Filtering Cores. Professional PowerCon 32 A Inlet Connector. 2 pole 25A Power Relay (breaking capacity 6500VA). GIGAWATT AUDIO GRADE Suppression Capacitors. Double Power Buffer System. Ultra-rigid, Non Magnetic Austenitic Steel Chassis with Bituminous Vibration Absorber. Voltage Display. Rolling-Ball Isolation System			
		with LS-2HC EVO cable	10 680 €
		with LS-1HC EVO cable	9 420 €
		with LC-3HC EVO cable	8 535 €
		with LC-2HC EVO cable	8 070 €
PC-3 SE EVO+ 6 outputs. DC Blocker. Distribution bars - silvered OFC 30 QMM. Internal wiring - silvered OFHC 4 QMM. Super-MSS Filtering Cores. 16A Relay (breaking capacity 4000VA). Double Power Buffer System. Highly Alloyed Steel Chassis with Bituminous Vibration Absorber. Voltage Display. Solid Aluminum Anti-vibration Feet.			
		with LS-2 EVO cable	8 310 €
		with LS-1 EVO cable	7 050 €
		with LC-3 EVO cable	6 195 €
		with LC-2 EVO cable	5 700 €
PC-3 EVO+ 6 outputs. DC Blocker. Distribution bars - OFC 30 QMM. Internal wiring - silvered OFHC 4 QMM. Super-MSS Filtering Cores. 16A Relay (breaking capacity 4000VA). Double Power Buffer System. Highly Alloyed Steel Chassis. Voltage Display. Solid Aluminum Anti-vibration Feet			
		with LS-1 EVO cable	5 850 €
		with LC-3 EVO cable	4 995 €
		with LC-2 EVO cable	4 500 €
		with LC-1 EVO cable	4 200 €
PC-2 EVO+ 6 outputs. DC Blocker. Distribution bars - OFC 30 QMM. Internal wiring - OFHC 2,5 QMM. Iron Powder Filtering Cores. 16A Relay (breaking capacity 4000VA). Double Power Buffer System. Highly Alloyed Steel Chassis. Solid Aluminum Anti-vibration Feet.			
		with LS-1 EVO cable	4 980 €
		with LC-3 EVO cable	4 125 €
		with LC-2 EVO cable	3 630 €
		with LC-1 EVO cable	3 330 €
POWERPRIME 6 outputs. Distribution bars OFC 30 QMM. Internal wiring OFHC 4,0 QMM. RLC Filtering Block. 16A Relay			
		with LC-3 EVO cable	3 015 €
		with LC-2 EVO cable	2 520 €
		with LC-1 EVO cable	2 220 €

Power Strips				
PF-2 EVO				
6 outputs. Metal Shielded Chassis. Distribution bars - OFC 30 QMM. Internal wiring - GigaWatt Powerlink OFHC 4 QMM. Advanced RLC filtering block. Iron Powder Filtering Cores. LED indicators of proper work and polarization.				
		with LC-3 EVO cable	1 920 €	
		with LC-2 EVO cable	1 425 €	
		with LC-1 EVO cable	1 125 €	
PF-1 EVO				
6 outputs. Metal Shielded Chassis. Distribution bars - OFC 30 QMM. Internal wiring - OFHC 4 QMM. Iron Powder Filtering Cores. LED.				
		with LC-2 EVO cable	855 €	
		with LC-1 EVO cable	555 €	
PF-1e				
6 outputs. Metal Shielded Chassis. Internal wiring - OFHC 2,5 QMM. Iron Powder Filtering Cores.				
		with LC-1 EVO cable	450 €	
		without cable	270 €	
Power Cables				
LS-2 EVO				
	Silver plated OFHC, solid-core, twisted conductors. FEP dielectric, Multi Layer PVC external isolation. Copper shield 100% coverage. SE version Loss-free Nano-crystal Alloys Passive Filter. G-050 SM/G-070 SM Metal Body, Rhodium Plated Plugs.		1,5 m	3 390 €
			next 0,5 m	1 140 €
LS-1 EVO				
	Silver plated OFHC, solid-core, twisted conductors. FEP dielectric, Multi Layer PVC external isolation. Copper shield 100% coverage. Loss-free Nano-crystal Alloys Passive Filter. G-010 CLS/G-030 CLS Rhodium Plated Plugs.		1,5 m	1 980 €
			next 0,5 m	660 €
LC-3 EVO				
	8x 1,6 QMM. OFHC multistrand (7 leads) conductors. PE dielectric. PVC external isolation. Aluminum foil static shield, 100% coverage. G-050 SM/G-070 SM Metal Body, Rhodium Plated Plugs.		1,5 m	1 095 €
			next 0,5 m	198 €
LC-2 EVO				
	7 x 1,5 QMM. OFHC solid-core conductors. PE dielectric. PVC external isolation. Aluminum foil static shield, 100% coverage. G-010/G-030 Gold Plated Plugs.		1,5 m	540 €
			1,0 m	495 €
			next 0,5 m	99 €
LC-1 EVO				
	5 x 1,5 QMM. OFHC solid-core conductors. PE dielectric. PVC external isolation. Aluminum foil static shield, 100% coverage. G-010/G-030 Standard Plugs.		1,5 m	210 €
			1 m	195 €
			next 0,5 m	36 €

Accessories			
	G-040 SCHUKO for Assembly		27 €
	G-044 SCHUKO Wall Socket		105 €
	G-044 Duplex SCHUKO Wall Socket		174 €
	IEC320-C5 / IEC320-C7 Plug Adapter		27 €
	LC-Y EVO 3X4 In-Wall Cable (1 meter)		30 €
	G-C16A Installation Circuit Breaker		85 €
	G-C16A 2P 2-Pole Installation Circuit Breaker		235 €
Options			
	Switch OFF the display for EVO series		30 €
	White LED display		105 €
	Rolling-Ball Isolation System Anti-Vibration Feet (4 pieces)		660 €
	DC Blocker for PowerPrime		300 €
DC Blocker upgrade			
	for PC-4 EVO+		1 350 €
	for PC-3 SE EVO+ / PC-3 EVO+		1 050 €
	for PC-2 EVO+ / PowerPrime		750 €