

Retail Price List - 2023

Focussing R&D, marketing and manufacturing at sites across the US, in Denmark and China with over a century of industry experience and leadership, Perlisten Audio offers music and home cinema enthusiasts a completely proprietary path to greater fidelity and value. Perlisten Audio is the first brand in the world to have received THX Dominus Certification, the newest and the largest performance class of THX Certification, designed to bridge the gap between large home theatre speakers and those used in movie houses worldwide.

Signature Series speakers (priced as singles)

RETAIL
inc VAT

MODEL S7t TOWER

Featuring proprietary DPC-Array of 28mm Beryllium dome and dual 28mm TPCD ultra-lightweight domes. All transducers are developed ground up by our engineers. Custom bass drivers made from thin-ply carbon diaphragms (TPCD) can be configured as bass reflex or acoustic suspension and adjusted for listener preference. **World's first loudspeakers to be certified for THX Dominus.**

Enclosure alignment: 4-way bass reflex/acoustic suspension

Driver complement: Flagship DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (4) Textreme TPCD

Sensitivity: 92dB/2.83V/1.0m

Impedance: 4Ω nominal/1.0m

Crossover Frequency: 500Hz, 1.1kHz, 4.4kHz

Frequency Response (+/-2dB): 80-20kHz

Frequency Response (-10dB): Bass reflex: 22-37kHz; Acoustic suspension: 32-37kHz

Dimensions (HxWxD): 1295x240x400mm

Weight: 55.7 kg

Recommended Amplifier Power: 100-600W RMS

SPL capability (100-20kHz): 117dB peak <2%-2nd, 3rd Harmonics

Certification: THX Dominus - large LCR



S7t High Gloss Ebony

21000 €

S7t High Gloss Black or White

18000 €

Retail Price List - 2023

Signature Series speakers

RETAIL
inc VAT

MODEL S7c CENTRE

FSimilar driver complement to the flagship S7T. THX Dominus certified.

Enclosure alignment: 4-way acoustic suspension

Driver complement: Flagship DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (4) Textreme TPCD

Sensitivity: 92dB/2.83V/1.0m

Impedance: 4Ω nominal/3.2Ω min

Crossover Frequency: 500Hz, 1.1kHz, 4.4kHz

Frequency Response (+/-2dB): 80-20kHz

Frequency Response (-10dB): 38-37kHz

Typical in room bass extension: 32Hz

Dimensions (HxWxD): 960x240x400mm

Weight: 33.5 kg

Recommended Amplifier Power: 100-600W RMS

SPL capability (100-20kHz): 117dB peak <2%-2nd, 3rd Harmonics

Certification: THX Dominus - LCR



High Gloss Ebony

8400 €

High Gloss Black or White

7400 €

MODEL S5t TOWER

A smaller version of the S7t with nearly the same SPL, sensitivity, and low frequency output.

Enclosure alignment: 3-way bass reflex / acoustic suspension

Driver complement: Flagship DPC-Array: 28mm (1) Beryllium; 28mm (2) Textreme TPCD; Woofers: 180mm(2) Textreme TPCD

Sensitivity: 89.5dB / 2.83v / 1.0m

Impedance: 4Ω nominal / 3.0Ω min

Response Linearity: 80 - 20kHz +/-1.5dB window

Frequency Response (-10dB): Bass reflex: 24 - 32kHz; Acoustic suspension: 36 - 32kHz

Typical In Room bass extension: Bass reflex: 20Hz; Acoustic suspension: 23Hz

Dimensions (HxWxD): 1119 x 240 x 400mm

Weight 43.2 kg

Recommended Amplifier Power 100 - 300W RMS

SPL capability @1m (100-20kHz): 114.3dB peak; 114.0dB peak <3% - 2nd, 3rd Harmonics

Certification: THX Dominus, THX Ultra



High Gloss Ebony

16000 €

High Gloss Black or White

14000 €

Retail Price List - 2023

Signature Series speakers

RETAIL
ex VAT

RETAIL
inc VAT

MODEL S5c CENTRE

A world class centre for slightly smaller rooms and screens, similar to the S7c with nearly the same SPL, sensitivity, and low frequency output.



Enclosure alignment: 3-way acoustic suspension

Driver complement: Flagship DPC Array: 28mm (1) Beryllium; 28mm (2) Textreme TPCD

Sensitivity: 88.8dB / 2.83v / 1.0m

Impedance: 4Ω nominal / 3.2Ω min

Response Linearity: 80 - 20kHz +/-1.5dB window

Frequency Response (-10dB): 42 - 34kHz

Typical in room bass extension: 33Hz

Dimensions (HxWxD): 4240 x 596 x 300mm

Weight: 21.4 kg

Recommended Amplifier Power: 100 - 300W RMS

SPL capability @1m (100-20kHz): 113.6dB peak; 111.0dB peak <3% - 2nd, 3rd Harmonics

Certification: THX Dominus, THX Ultra



High Gloss Ebony

6500 €

High Gloss Black or White

5500 €

MODEL S5m MONITOR

Features Perlisten DPC array and two 180mm Textreme TPCD woofers. THX Dominus certified.



Enclosure alignment: 3-way bass reflex/acoustic suspension

Driver complement: Flagship DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (2) Textreme TPCD

Sensitivity: 89.6dB/2.83V/1.0m

Impedance: 4Ω nominal/3.0 Ω min

Frequency Response (+/-1.5dB): 80-20kHz

Frequency Response (-10dB): Bass reflex: 35-37kHz; Acoustic suspension: 71-37kHz

Typical in room bass extension: Bass reflex: 29Hz; Acoustic suspension: 32Hz

Dimensions (HxWxD) without stand: 600x240x400mm Weight: 19.0 kg

Recommended Amplifier Power: 50-300W RMS

SPL capability (100-20kHz): 117dB peak <2%-2nd, 3rd Harmonics

Certification: THX Dominus; THX Ultra



High Gloss Ebony

14000 €

High Gloss Black or White

12500 €

Retail Price List - 2023

Signature Series speakers

RETAIL
ex VAT

RETAIL
inc VAT

MODEL S4b BOOKSHELF

For use in 2.1 systems or as surround, height or LCR in a cinema system using subwoofers. Bookshelf, stand or on-wall mounting with keyhole or available bracket. Features DPC-Array and single 180mm Textreme TPCD woofer. THX Dominus certified.

Enclosure alignment: 3-way acoustic suspension

Driver complement: Flagship DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (1) Textreme TPCD

Sensitivity: 85.4dB / 2.83V / 1.0m

Impedance: 4Ω nominal/3.2Ω min

Frequency Response (+/-1.5dB): 100 - 20kHz

Frequency Response (-10dB): 36 - 37kHz

Typical in room bass extension: 30Hz

Dimensions (HxWxD) without stand: 420 x 240 x 185mm

Weight: 11.0 kg

Recommended Amplifier Power: 50 - 300W RMS

SPL capability (100-20kHz): 111dB peak <2% - 2nd, 3rd Harmonics

Certification: THX Dominus



High Gloss Ebony

9950 €

High Gloss Black or White

8000 €

MODEL S4s SURROUND

Designed for on-wall or flushed-in (2pi) applications as surround, height or LCR. High sensitivity, power handling and low distortion make S4s the ideal choice as a surround speaker for high-end cinemas. Features DPC-Array and single single 180mm Textreme TPCD woofer. THX Dominus certified.

Enclosure alignment: 3-way acoustic suspension

Driver complement: Flagship DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (1) Textreme TPCD

Sensitivity: 89.6dB/2.83V/1.0m

Impedance: 4Ω nominal/3.2Ω min

Frequency Response (+/-1.5dB): 100 - 20kHz

Frequency Response (-10dB): 39 - 37kHz

Typical in room bass extension: 33Hz

Dimensions (HxWxD) without stand: 405x240x185mm

Weight: 9.5 kg

Recommended Amplifier Power: 50 - 300W RMS

SPL capability (100-20kHz): 111dB peak <2% - 2nd, 3rd Harmonics

Certification: THX Dominus; THX Ultra



High Gloss Black or White

8000 €

Retail Price List - 2023

Dominus certified in-wall speaker

RETAIL
inc VAT

Perlisten S7i-LR

The award-winning flagship S7t design adapted for THX Dominus Certified in-wall applications.

Enclosure Alignment: 4-way acoustic suspension

Driver complement: DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (4) Textreme TPCD

Sensitivity: 91.9dB / 2.83V / 1.0m

Impedance: 4Ω nominal / 3.4Ω min

Response Linearity: 80 - 20kHz +/-1.5dB window

Frequency Response (-10dB): 45 - 37kHz

Typical In Room bass extension: 37Hz

Dimensions (HxWxD): 1036.6 x 298.6 x 111.2mm


Mounting Dimensions (HxWxD): 996 x 257 x 101.7mm

Weight: 26.4 kg

Recommended Amplifier Power: 100 - 600W RMS

SPL capability @1m (100-20kHz): 119.7dB peak; 117.0dB peak <3% 2nd, 3rd Harmonics

Certification: THX Dominus



S7i-LR

7500 €/Unid

Perlisten S7i-C

The award-winning flagship S7t design adapted for THX Dominus Certified in-wall centre-channel applications.

Enclosure Alignment: 4-way acoustic suspension

Driver complement: DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (4) Textreme TPCD

Sensitivity: 92.0dB / 2.83V / 1.0m

Impedance: 4Ω nominal / 3.4Ω min

Response Linearity: 80 - 20kHz +/-1.5dB window

Frequency Response (-10dB): 45 - 37kHz

Typical In Room bass extension: 39Hz

Dimensions (HxWxD): 298.6 x 1036.6 x 111.2mm


Mounting Dimensions (HxWxD): 257 x 996 x 101.7mm

Weight: 26.4 kg

Recommended Amplifier Power: 100 - 600W RMS

SPL capability @1m (100-20kHz): 119.8dB peak; 117.0dB peak <3% 2nd, 3rd Harmonics

Certification: THX Dominus



S7i-C

7500 €/Unid

Retail Price List - 2023


Dominus certified in-wall speaker

RETAIL
inc VAT

Perlisten S5i-LR

The award-winning S5m design adapted for THX Dominus Certified in-wall applications.

Enclosure Alignment: 3-way acoustic suspension
 Driver complement: DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (2) Textreme TPCD
 Sensitivity: 91.9dB / 2.83V / 1.0m
 Impedance: 4Ω nominal / 3.4Ω min
 Response Linearity: 80 - 20kHz +/-1.5dB window
 Frequency Response (-10dB): 52 - 37kHz
 Typical In Room bass extension: 46Hz
 Dimensions (HxWxD): 624 x 257 x 101.7mm
 Mounting Dimensions (HxWxD): 624 x 257 x 101.7mm
 Weight: 15.9 kg
 Recommended Amplifier Power: 100 - 350W RMS
 SPL capability @1m (100-20kHz): 117.3dB peak; 117.0dB peak <3% 2nd, 3rd Harmonics
 Certification: THX Dominus




S5i-LR

6500 €/Unid

Perlisten S5i-C

The award-winning S5m design adapted for THX Dominus Certified in-wall centre channel applications.

Enclosure Alignment: 3-way acoustic suspension
 Driver complement: DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (2) Textreme TPCD
 Sensitivity: 91.6dB / 2.83V / 1.0m
 Impedance: 4Ω nominal / 3.4Ω min
 Response Linearity: 80 - 20kHz +/-1.5dB window
 Frequency Response (-10dB): 50 - 37kHz
 Typical In Room bass extension: 42Hz
 Dimensions (HxWxD): 298 x 665 x 111mm
 Mounting Dimensions (HxWxD): 257 x 624 x 101.7mm
 Weight: 15.9 kg
 Recommended Amplifier Power: 100 - 350W RMS
 SPL capability @1m (100-20kHz): 117.0dB peak; 117.0dB peak <3% 2nd, 3rd Harmonics
 Certification: THX Dominus



S5i-C

6500 €/Unid

Retail Price List - 2023

Dominus certified in-wall speaker

RETAIL
inc VAT

Perlisten S4i-LCRS

The award-winning S4s/S4b designs adapted for THX Dominus Certified in-wall surround channel applications.

Enclosure Alignment: 3-way acoustic suspension

Driver complement: DPC Array: 28mm Beryllium, 28mm (2) Textreme TPCD; Woofers: 180mm (1) Textreme TPCD

Sensitivity: 88.0dB / 2.83V / 1.0m

Impedance: 4Ω nominal / 3.4Ω min

Response Linearity: 80 - 20kHz +/-1.5dB window

Frequency Response (-10dB): 42 - 37kHz

Typical In Room bass extension: 38Hz

Dimensions (HxWxD): 479 x 298 x 111mm


Mounting Dimensions (HxWxD): 438 x 257 x 101.7mm

Weight: 11.2 kg

Recommended Amplifier Power: 50 - 250W RMS

SPL capability @1m (100-20kHz): 112.0dB peak; 111.0dB peak <3% 2nd, 3rd Harmonics

Certification: THX Dominus Surround, Ultra LCR



S4i-LCRS

3900 €/Unid

Retail Price List - 2023

Reference Series speakers (priced as singles)

RETAIL
inc VAT

MODEL R7t TOWER

Two-channel high fidelity speaker with the versatility to be used in multi-channel systems. Featuring DPC-Array of three 26mm silk domes and twin 165mm HFP woofers, which can be aligned as bass reflex or acoustic suspension depending on specific tastes. THX Dominus certified.

Enclosure Alignment: 4-way bass reflex / acoustic suspension

Driver complement: DPC-Array: 26mm(3) Silk dome, woofers: 165mm (4) HPF diaphragms

Sensitivity: 90.0dB/2.83V/1.0m

Impedance: 4Ω nominal/3.1Ω min

Response Linearity 80 - 20kHz +/-1.5dB

Frequency Response (-10dB): Bass reflex: 27 - 32kHz; Acoustic suspension: 38 - 32kHz


Typical In Room bass extension: bass reflex: 19Hz; acoustic suspension: 30Hz

Dimensions (HxWxD): 1268 x 230 x 350mm Weight: 48.0 kg

Recommended Amplifier Power: 100 - 400W RMS

SPL capability @1m (100-20kHz): 116.0dB peak <3% - 2nd, 3rd Harmonics

Certification: THX Dominus; THX Ultra



R7t (high gloss black)

9500 €

MODEL R5t TOWER

Two-channel high fidelity speaker with the versatility to be used in multi-channel systems. Featuring DPC-Array of three 26mm silk domes and twin 165mm HFP woofers, which can be aligned as bass reflex or acoustic suspension depending on specific tastes. THX Dominus certified.

Enclosure alignment: 3-way bass reflex / acoustic suspension

Driver complement: DPC Array: 26mm(3) Silk dome, woofers: 165mm (2) HPF diaphragms

Sensitivity: 89dB/2.83V/1.0m

Impedance: 4Ω nominal/3.2Ω min

Crossover Frequency: 1.25Hz, 4.4kHz

Frequency Response (+/-2dB): 80 - 20kHz

Frequency Response (-10dB): Bass reflex: 24 - 32kHz; Acoustic suspension: 38 - 32kHz

Typical in room bass extension: Bass reflex: 21Hz; Acoustic suspension: 32Hz

Dimensions (HxWxD): 1100x230x350mm Weight: 26.5 kg

Recommended Amplifier Power: 100-250W RMS

SPL capability (100-20kHz): 111dB peak <2%-2nd, 3rd Harmonics

Certification: THX Dominus; THX Ultra



R5t (high gloss black)

6950 €

Retail Price List - 2023

Reference Series speakers

RETAIL
inc VAT

MODEL R5c CENTRE

Designed to be mounted on optional stand, or wall mounted using dedicated tilt/swivel bracket. Featuring DPC-Array of three 26mm silk domes and twin 165mm HFP woofers. THX Dominus certified.

Enclosure Alignment: 3-way acoustic suspension

Driver compliment: DPC-Array: 26mm (3) Silk dome, woofers: 165mm(2) HPF diaphragms

Sensitivity: 88.6dB/2.83V/1.0m

Impedance: 4Ω nominal / 3.4Ω min

Response Linearity: 80 - 20kHz +/-1.5dB

Frequency Response (-10dB): 49 - 32kHz

Typical In Room bass extension: 44Hz

Dimensions (HxWxD): 240 x 550 x 270mm

Weight: 15.0 kg

Recommended Amplifier Power: 100 - 250W RMS

SPL capability @1m (100-20kHz): 112.6dB peak <3% - 2nd, 3rd Harmonics

Certification: THX Dominus, THX Ultra



R5c (high gloss black)

3000 €

MODEL R5m MONITOR

Designed to be mounted on optional stand, or wall mounted using dedicated tilt/swivel bracket. Featuring DPC-Array of three 26mm silk domes and twin 165mm HFP woofers. THX Dominus certified.

Enclosure Alignment: 3-way bass reflex / acoustic suspension

Driver compliment: DPC-Array: 26mm (3) Silk dome, woofers: 165mm (2) HPF diaphragms

Sensitivity: 89.2dB/2.83V/1.0m

Impedance: 4Ω nominal / 2.7Ω min

Response Linearity: 80 - 20kHz +/-1.5dB

Frequency Response (-10dB): bass reflex: 40 - 32kHz; acoustic suspension: 47 - 32kHz

Typical In Room bass extension: bass reflex: 37Hz; acoustic suspension: 43Hz

Dimensions (HxWxD): 546 x 230 x 336mm

Weight: 17.5 kg

Recommended Amplifier Power: 100 - 250W RMS

SPL capability @1m (100-20kHz): 113.2dB peak <3% - 2nd, 3rd Harmonics

Certification: THX Dominus, THX Ultra



R5m (high gloss black)

6000 €

Retail Price List - 2023

Reference Series speakers

RETAIL
inc VAT

MODEL R4b BOOKSHELF

Designed to be mounted on optional stand, or wall mounted using dedicated tilt/swivel bracket. Featuring DPC-Array of three 26mm silk domes and single 165mm HFP woofer. THX Ultra certified.

Enclosure Alignment: 3-way acoustic suspension

Driver complement: DPC-Array: 26mm (3) Silk dome, woofers: 165mm HPF diaphragm

Sensitivity: 84.6dB/2.83V/1.0m

Impedance: 4Ω nominal / 3.8Ω min

Response Linearity: 80 - 20kHz +/-1.5dB

Frequency Response (-10dB): 45 - 32kHz

Typical In Room bass extension: 38Hz

Dimensions (HxWxD): 382 x 230 x 336mm

Weight: 9.5 kg

Recommended Amplifier Power: 50 - 200W RMS

SPL capability @1m (100-20kHz): 107.6dB peak <3% - 2nd, 3rd Harmonics

Certification: THX Ultra



R4b (high gloss black)

4950 €

MODEL R4s SURROUND/HEIGHT

Designed to be mounted on optional stand, or wall mounted using dedicated tilt/swivel bracket. Featuring DPC-Array of three 26mm silk domes and single 165mm HFP woofer. THX Ultra certified.

Enclosure Alignment: 3-way acoustic suspension

Driver complement: DPC-Array: 26mm (3) Silk dome, woofers: 165mm HPF diaphragm

Sensitivity: 86.5dB/2.83V/1.0m

Impedance: 4Ω nominal / 3.7Ω min

Response Linearity: 300 - 20kHz +/-1.5dB

Frequency Response (-10dB): 48 - 32kHz

Typical In Room bass extension: 42Hz

Dimensions (HxWxD): 378 x 230 x 173mm

Weight: 9.5 kg

Recommended Amplifier Power: 50 - 200W RMS

SPL capability @1m (100-20kHz): 109.5dB peak <3% - 2nd, 3rd Harmonics

Certification: THX Ultra



R4s (high gloss black)

3600 €

Retail Price List - 2023

Dominus/Ultra certified in-wall speaker

RETAIL
inc VAT

Perlisten R5i-LR

The R5m design adapted for THX Dominus Certified in-wall applications.

Enclosure Alignment: 3-way acoustic suspension

Driver complement: DPC Array: 26mm (3) Silk Dome; Woofers: 165mm (2) HPF

Sensitivity: 89.2dB / 2.83V / 1.0m

Impedance: 4Ω nominal / 3.4Ω min

Response Linearity: 80 - 20kHz +/-1.5dB window

Frequency Response (-10dB): acoustic suspension 39 - 32kHz

Typical In Room bass extension: acoustic suspension 34Hz

Dimensions (HxWxD): 665 x 298 x 111mm


Mounting Dimensions (HxWxD): 624 x 257 x 101.7mm

Weight: 15.9 kg

Recommended Amplifier Power: 50 - 250W RMS

SPL capability @1m (100-20kHz): 113.2dB peak; 111.0dB peak <3% 2nd, 3rd Harmonics

Certification: THX Dominus, THX Ultra



R5i-LR

3000 €/Unid

Perlisten R5i-C

The R5c design adapted for THX Dominus Certified in-wall applications.

Enclosure Alignment: 3-way acoustic suspension

Driver complement: DPC Array: 26mm (3) Silk Dome; Woofers: 165mm (2) HPF

Sensitivity: 89.4dB / 2.83V / 1.0m

Impedance: 4Ω nominal / 3.4Ω min

Response Linearity: 80 - 20kHz +/-1.5dB window

Frequency Response (-10dB): acoustic suspension 40 - 32kHz

Typical In Room bass extension: acoustic suspension 34Hz

Dimensions (HxWxD): 298 x 665 x 111mm


Mounting Dimensions (HxWxD): 257 x 624 x 101.7mm

Weight: 15.9 kg

Recommended Amplifier Power: 50 - 250W RMS

SPL capability @1m (100-20kHz): 113.4dB peak; 111.0dB peak <3% 2nd, 3rd Harmonics

Certification: THX Dominus, THX Ultra



R5i-C

3000 €/Unid

Retail Price List - 2023

Dominus/Ultra certified in-wall speaker

RETAIL
inc VAT

Perlisten R4i-LCRS

The R4s/R4b designs adapted for THX Dominus Certified in-wall surround channel applications.

Enclosure Alignment: 3-way acoustic suspension

Driver complement: DPC Array: 26mm (3) Silk Dome; Woofers: 165mm (1) HPF

Sensitivity: 88.8dB / 2.83V / 1.0m

Impedance: 4Ω nominal / 3.4Ω min

Response Linearity: 100 - 20kHz +/-1.5dB window

Frequency Response (-10dB): 46 - 37kHz

Typical In Room bass extension: 40Hz

Dimensions (HxWxD): 479 x 298 x 111mm


Mounting Dimensions (HxWxD): 438 x 257 x 101.7mm

Weight: 11.2 kg

Recommended Amplifier Power: 50 – 200W RMS

SPL capability @1m (100-20kHz): 111.8dB peak; 111.0dB peak <3% 2nd, 3rd Harmonics

Certification: THX Dominus Surround, THX Ultra LCR



R4i-LCRS

2600 €/Unid

Retail Price List - 2023

D-Series Subwoofers

RETAIL
inc VAT

MODEL D215s SUBWOOFER

Push-pull driver configuration. Carbon fibre composite diaphragms. Aluminium shorting rings, massive magnets, multi-layer Nomex spiders and lightweight aluminium voice coils. Proprietary 3.0kW amplifier controlled by a 48-bit data bath DSP and 32-bit ARM M4 Cortex processor. All D-Series subs feature a 2.4" LCD touchscreen display and the ability to control advance settings using Perlisten's App. THX Dominus certified.

Alignment: Push-Pull, acoustic suspension

Amplifier: 3.0kW RMS short term

Display Interface: 2.4" LCD colour touchscreen

App: iOS and Android

Processor: 32-bit ARM Cortex M4, double precision floating point math

DSP Engine: Ti DSP 48-bit data paths

Driver complement: (2) 380mm Carbon fibre diaphragm, +/-30mm linear excursion

Reference sensitivity: 92dB / 150mV/ 1.0m

Frequency Response: THX EQ 20-200Hz (-6dB) / 16-210Hz (-10dB);

Boost (Large Room) EQ 15-200Hz (-6dB) / 13-210Hz (-10dB); Cut (Small Room) EQ 24-200Hz (-6dB) / 18-210Hz (-10dB)

Inputs: (2) Balanced XLR; (2) Unbalanced RCA

Outputs: (2) Balanced XLR unbuffered; (2) Unbalanced RCA unbuffered

Parametric EQ: 10-Band PEQ with 3 user presets

Low Pass filter: bypass, 30-160Hz, slope 6,12,18,24dB/oct

Phase: variable 0-270°

Polarity: normal / inverted

Configurable Auto turn-on and 12V Trigger: XLR 1, XLR 1+2, RCA 1, RCA 1+2

Dimensions (HxWxD): 805 x 500 x 650.5mm

Weight: 92.0 kg

Certification: THX Dominus



D215s (piano black)

9450 €

Retail Price List - 2023

D-Series Subwoofers

RETAIL

RETAIL
inc VAT

MODEL D212s SUBWOOFER

Push-pull driver configuration. Carbon fibre composite diaphragms. Aluminium shorting rings, massive magnets, multi-layer Nomex spiders and lightweight aluminium voice coils. Proprietary 3.0kW amplifier controlled by a 48-bit data bath DSP and 32-bit ARM M4 Cortex processor. All D-Series subs feature a 2.4" LCD touchscreen display and the ability to control advance settings using Perlisten's App. THX Dominus certified.

Alignment: Push-Pull, acoustic suspension

Amplifier: 3.0kW RMS short term

Display Interface: 2.4" LCD colour touchscreen

App: iOS and Android

Processor: 32-bit ARM Cortex M4, double precision floating point math

DSP Engine: Ti DSP 48-bit data paths

Driver compliment: (2) 300mm, Carbon fibre diaphragm +/-30mm linear excursion

Frequency Response: THX EQ 20-231Hz (-6dB) / 16-245Hz (-10dB); Boost (Large Room) EQ 15-231Hz (-6dB) / 13.5-245Hz (-10dB); Cut (Small Room) EQ 24-231Hz (-6dB) / 18-245Hz (-10dB)

Inputs: (2) Balanced XLR; (2) Unbalanced RCA

Outputs: (2) Balanced XLR unbuffered; (2) Unbalanced RCA unbuffered

Parametric EQ: 10-Band PEQ with 3 user presets

Low Pass filter: Bypass, 30-160Hz, slope 6,12,18,24dB/oct

Phase: Variable 0-270°

Polarity: Normal / inverted

Configurable Auto turn-on and 12V Trigger: XLR 1, XLR 1+2, RCA 1, RCA 1+2

Dimensions (HxWxD): 668 x 420 x 550mm

Weight: 68.0 kg

Certification: THX Dominus



D212s (piano black)

7350 €

Retail Price List - 2023

D-Series Subwoofers

RETAIL
inc VAT

MODEL D15s SUBWOOFER

The D15s is the smallest single THX Dominus certified sub available. Proprietary 2.0kW amplifier controlled by a 48-bit data bath DSP and 32-bit ARM M4 Cortex processor. Carbon fibre composite diaphragms, multiple aluminium shorting rings, massive magnets, multi-layer Nomex spiders and lightweight aluminium voice coils. 2.4" LCD touchscreen display and Perlisten App control.

Alignment: Acoustic suspension

Amplifier: 2.0kW RMS short term

Display Interface: 2.4" LCD colour touchscreen

App: iOS and Android

Processor: 32-bit ARM Cortex M4, double precision floating point math

DSP Engine: Ti DSP 48-bit data paths

Driver compliment: 380mm, Carbon fibre diaphragm +/-30mm linear excursion

Reference sensitivity: 92dB / 150mV/ 1.0m

Frequency Response: THX EQ 20-320Hz (-6dB) / 16-395Hz (-10dB);

Boost (Large Room) EQ 16-320Hz (-6dB) / 14-395Hz (-10dB); Cut (Small Room) EQ 24-320Hz (-6dB) / 18-395Hz (-10dB)

Inputs: (2) Balanced XLR; (2) Unbalanced RCA

Outputs: (2) Balanced XLR unbuffered; (2) Unbalanced RCA unbuffered

Parametric EQ: 10-Band PEQ with 3 user presets

Low Pass filter: Bypass, 30-160Hz, slope 6,12,18,24dB/oct

Phase: Variable 0-270°

Polarity: Normal / inverted

Configurable Auto turn-on and 12V Trigger: XLR 1, XLR 1+2, RCA 1, RCA 1+2

Dimensions (HxWxD): 528 x 500 x 500mm

Weight: 46.0 kg

Certification: THX Dominus



D15s (piano black)

5250 €

Retail Price List - 2023

D-Series Subwoofers

RETAIL
inc VAT

MODEL D12s SUBWOOFER

The smallest subwoofer in the series yet packs enough punch to be certified THX Dominus using a pair of D12s subs. Proprietary 1.5kW amplifier controlled by a 48-bit data bath DSP and 32-bit ARM M4 Cortex processor. Carbon fibre composite diaphragms, multiple aluminium shorting rings, massive magnets, multi-layer Nomex spiders and lightweight aluminium voice coils. 2.4" LCD touchscreen display and Perlisten App control.



Alignment: Acoustic suspension

Amplifier: 1.5kW rms short term

Display Interface: 2.4" LCD colour touchscreen

App: iOS and Android

Processor: 32-bit ARM Cortex M4, double precision floating point math

DSP Engine: Ti DSP 48-bit data paths

Driver complement: 300mm, Carbon fibre diaphragm +/-30mm linear excursion

Reference sensitivity: 92dB / 150mV/ 1.0m

Frequency Response: THX EQ 20-289Hz (-6dB) / 16-330Hz (-10dB);

Boost (Large Room) EQ 16-289Hz (-6dB) / 14-330Hz (-10dB); Cut

(Small Room) EQ 25-289Hz (-6dB) / 19-330Hz (-10dB)

Inputs: (2) Balanced XLR; (2) Unbalanced RCA

Outputs: (2) Balanced XLR unbuffered; (2) Unbalanced RCA unbuffered

Parametric EQ: 10-Band PEQ with 3 user presets

Low Pass filter: Bypass, 30-160Hz, slope 6,12,18,24dB/oct

Polarity: Normal / inverted

Configurable Auto turn-on and 12V Trigger: XLR 1, XLR 1+2, RCA 1, RCA 1+2

Dimensions (HxWxD): 448 x 420 x 450mm Weight: 41.0 kg

Certification: THX Dominus (in pairs)

D12s (piano black)

4200 €

Retail Price List - 2023

D-Series Subwoofers

RETAIL
inc VAT

MODEL R212s SUBWOOFER

The R212s is a 2x12" push-pull active subwoofer, powered by a proprietary 1.3kW amplifier. All functions and safeties are controlled by a 48-bit data path DSP and 32-bit ARM M4 Cortex processor. Control is via 2.4" LCD touchscreen display and smartphone app. Certified THX Dominus when two R212s subs are used.

Alignment: Push-Pull, acoustic suspension

Amplifier: 1.3kW rms short term

Display Interface: 2.4" LCD colour touchscreen

App: iOS and Android

Processor: 32-bit ARM Cortex M4, double precision floating point math

DSP Engine: Ti DSP 48-bit data paths

Driver complement: (2)300mm, Glass fibre diaphragm +/-20mm linear excursion

Frequency Response: THX EQ 20-256Hz (-6dB) / 16-278Hz (-10dB);
Boost (Large Room) EQ 16-256Hz (-6dB) / 14-278Hz (-10dB); Cut
(Small Room) EQ 25-256Hz (-6dB) / 19-278Hz (-10dB)

Inputs: (2) Balanced XLR; (2) Unbalanced RCA

Outputs: (2) Balanced XLR unbuffered; (2) Unbalanced RCA unbuffered

Parametric EQ: 10-Band PEQ with 3 user presets

Low Pass filter: bypass, 30-160Hz, slope 6,12,18,24dB/oct

Phase: Variable 0-270°

Polarity: Normal / inverted

Configurable Auto turn-on and 12v Trigger: XLR 1, XLR 1+2, RCA 1, RCA 1+2

Dimensions (HxWxD): 600 x 410 x 500mm

Weight: 48.2 kg

Certification: THX Dominus (2), THX Ultra (1)

Available finishes: Piano black



R212s

5700 €

Retail Price List - 2023

D-Series Subwoofers

RETAIL
inc VAT

MODEL R210s SUBWOOFER

The R210s is a 2x10" push-pull active subwoofer, powered by a proprietary 1.3kW amplifier. All functions and safeties are controlled by a 48-bit data path DSP and 32-bit ARM M4 Cortex processor. Control is via 2.4" LCD touchscreen display and smartphone app. Certified THX Dominus when four R210s subs are used.

Alignment: Push-Pull, acoustic suspension

Amplifier: 1.3kW rms short term

Display Interface: 2.4" LCD colour touchscreen

App: iOS and Android

Processor: 32-bit ARM Cortex M4, double precision floating point math

DSP Engine: Ti DSP 48-bit data paths

Driver complement: (2)250mm, Glass fibre diaphragm +/-20mm linear excursion

Frequency Response: THX EQ 20-256Hz (-6dB) / 16-278Hz (-10dB);
Boost (Large Room) EQ 16-256Hz (-6dB) / 14-302Hz (-10dB); Cut
(Small Room) EQ 25-290Hz (-6dB) / 19-302Hz (-10dB)

Inputs: (2) Balanced XLR; (2) Unbalanced RCA

Outputs: (2) Balanced XLR unbuffered; (2) Unbalanced RCA unbuffered

Parametric EQ: 10-Band PEQ with 3 user presets

Low Pass filter: bypass, 30-160Hz, slope 6,12,18,24dB/oct

Phase: Variable 0-270°

Polarity: Normal / inverted

Configurable Auto turn-on and 12v Trigger: XLR 1, XLR 1+2, RCA 1, RCA 1+2

Dimensions (HxWxD): 545 x 380 x 450mm

Weight: 44.0 kg

Certification: THX Dominus (4), THX Ultra (1)

Available finishes: Piano black



R210s

4600 €

Retail Price List - 2023

| Accessories | | | RETAIL inc VAT |
|--------------|------------------------------------|--|-------------------|
| SSLR-HGB | S Series stand L/R pair | | 1590 € |
| SSC-HGB | S Series Centre stand | | 795 € |
| RSLR-HGB | R Series Stand L/R pair | | 1450 € |
| RSC-HGB | R Series Centre stand | | 680 € |
| R/S-BRCKT | S/R Series wall bracket up to 25kg | | 85 € |
| Grille R-Ser | R Series round grille | | 65 € |