

KEF PRICE LIST

January 2025 Edition





KEF is a proud pioneer of excellence in sound

Since 1961, KEF has been obsessed with the power of high-fidelity; with its ability to shape and enhance the lives of listeners, and to transform the experience of sound from the ordinary to the visceral.

With innovation at our core and passion in our hearts, we are committed to engineering exceptional products and transformative experiences that bring meaning, magic, and moments into every home.

We continue to follow our founding vision to be the best at what we do, and to create a world in which listeners and creators can be inspired and supported to listen with intent and to believe with confidence.

'Of all art, music is the most indefinable and the most expressive, the most insubstantial and the most immediate, the most transitory and the most imperishable. Transformed to a dance of electrons along a wire, its ghost lives on. When KEF returns music to its rightful habitation, your ears and mind, they aim to do so in the most natural way they can... without drama, without exaggeration, without artifice.'

Raymond Cooke

KEF founder

Index

4	Listen and believe	
5	KEF Technologies	
6	HiFi Speakers & Accessories	
8		Muon
10		Blade
12		The Reference
16		R Series
20		Q Series
24		LS50 Meta
26		T Series
30	Wireless HiFi Speakers & Accessories	
32		LS60 Wireless
32		LS50 Wireless II
34		LSXII
34		LSXII LT

36	Headphones & Accessories	
39		Mu7
39		Mu3

42	Subwoofers & Accessories	
45		Reference 8b
45		KC92
46		KC62
46		Kube 15 MIE
46		Kube 12 MIE
46		Kube 10 MIE
47		Kube 8 MIE
47		T2

48	Architectural Speakers & Accessories	
51		Extreme Home Theatre
54		In-ceiling & in-wall
59		Special applications
62		Installed subwoofers
64		Outdoor

Listen and believe

KEF's mission is to deliver sound with as little intervention as possible; from treble to bass, and everything in between.

We believe that the best sound is natural sound. Combining our obsessions with acoustic authenticity and innovative engineering, our products speak for themselves.



KEF Technologies

A list of breakthroughs spanning more than half a century shores up that promise; a walk to match the talk. Patents and academic papers alike testify to decades of consistent progress, from the early use of synthetic materials to our Reference Series which determines industry standards to this day. KEF's insistence on excellence is at the heart of a virtuous circle, which attracts the world's most gifted acoustic engineers to join us in the pursuit of good, better, best.



Uni-Q® Technology

Of the many landmark innovations KEF has pioneered, arguably the greatest of all is the Uni-Q® driver array. Uni-Q® acts as a single point source to disperse sound more evenly, delivering a more coherent, hyper-realistic sound experience.



Metamaterial Absorption Technology (MAT™)

Metamaterial Absorption Technology (MAT™) is a highly complex maze-like structure that absorbs 99% of the unwanted sound from the rear of the driver, eliminating the resulting distortion and providing purer, more natural sound.



Single Apparent Source Technology

A unique technology that aims to achieve the acoustic ideal of a point source, where low, mid and high frequencies radiate from one point. The result is noticeably more precise imaging and highly accurate sound across a wider area.



Uni-Core™ Technology

Uni-Core™ technology redefines the physical space high-performance speakers and subwoofers required to deliver deep and accurate bass. Through exceptional engineering and creativity, KEF's engineers have revolutionised the traditional force-cancelling arrangement with a Uni-Core™ design that delivers deeper bass from ultra-compact cabinets.



Music Integrity Engine® (MIE)

Music Integrity Engine is a collection of bespoke Digital Signal Processing algorithms that is optimised for the Uni-Q driver, enabling it to deliver a perfectly timed performance, for better imaging and a tighter sound.

HiFi Speakers & Accessories



Muon

Sound by KEF.

Design by Ross Lovegrove.



The ultimate loudspeaker with state-of-the-art acoustic technology with the sensual, organic forms of the visionary industrial designer Ross Lovegrove. Muon is limited to an edition of 100 pairs.

Key Features

- Each Muon is individually crafted and comes with a certificate of its unique frequency response curve
- Feature Uni-Q driver array to deliver seamless imaging throughout the room
- Acoustic Compliance Enhancement (ACE) technology to double the available volume through adsorption
- Constructed from 6mm, super-formed aluminium to provide a totally rigid structure that minimises sound-distorting vibrations

Key Technologies

- Uni-Q®
- Acoustic Compliance Enhancement (ACE)

Muon

A triumph of form marrying function, Muon is perhaps the most extraordinary loudspeaker ever conceived.



MSRP
€200,000/pair

PRODUCT SPECIFICATION

Design	Four-way closed box floorstanding loudspeaker ACE enclosure
Drive units	6 x 250 mm (10 in.) LF 1 x 250 mm (10 in.) LMF Uni-Q driver array MF 1 x 125 mm (5 in.) Li-Mg-Al/LCP hybrid cone HF 1 x 25 mm (1 in.) vented aluminium dome, featuring KEF's unique 'Tangerine Waveguide'
Frequency response	4 Ω (min. 3.2 Ω)
Amplifier requirements	100 to 400 W (typical)
Sensitivity	90 dB (2.83V/1m)
Maximum output	118 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H2000 x W600 x D380 mm (78.7 x 23.6 x 15 in.)/piece
Product weight	115 kg/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H2160 x W850 x D700 mm (85 x 33.5 x 27.6 in.)/piece
Gross weight	180 kg (396.9 lbs.)/piece
Warranty period	5 years
Finishes	Polished Aluminium
Item no.	SP3582AA
UPC	637203027727



Blade

A sound statement.
An icon that engages every sense.



A bold and striking presence, Blade pushes the boundaries of what is possible with sound. The world's first Single Apparent Source loudspeaker now with Metamaterial Absorption Technology (MAT™).

Key Features

- Single Apparent Source technology revolutionises the orientation of the low, mid, and high frequency drivers to deliver sound you hear to be more real and immersive
- Metamaterial Absorption Technology eliminates 99% of high-frequency distortion for pure, natural sound
- Bespoke 12th generation Uni-Q with MAT driver array for exceptional acoustic accuracy
- Two pairs of force-cancelling LF drivers deliver clean, massively extended bass
- Enhanced crossover design with fine-tuned signal paths for maximum clarity
- Optimised cabinet design for best acoustic performance
- Customised finishes are available upon request

Key Technologies

- Uni-Q®
- MAT™
- Single Apparent Source Technology

Blade One Meta

Blade One Meta is the top model of Blade, the pinnacle of KEF engineering.



MSRP
€35,000/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex Single apparent source
Drive units	Uni-Q driver array HF: 25 mm (1 in.) aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 4 x 225 mm (9 in.) aluminium cone, force cancelling
Frequency response	35 Hz - 35 kHz
Amplifier requirements	50 - 400 W
Sensitivity	88 dB
Maximum output	117 dB
Impedance	4 Ω (min. 2.8 Ω)
Dimensions	H1590 x W363 x D540 mm (62.5 x 14.3 x 21.2 in./piece)
Product weight	57.2 kg (126 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H1680 x W454 x D704 mm (66.1 x 17.8 x 27.7 in./piece)		
Gross weight	681 kg (1501 lbs./piece)		
Warranty period	5 years		
Finishes	a. Piano Black/Grey	b. Piano Black/Copper	c. Frosted Blue/Blue
Item no.	SP4044BA	SP4044ZA01	SP4044CA
UPC	637203048371	637203048418	637203048388
Finishes	d. Frosted Blue/Bronze	e. Charcoal Grey/Red	f. Charcoal Grey/Bronze
Item no.	SP4044ZA03	SP4044ZA02	SP4044HA
UPC	637203048432	637203048425	637203048395
Finishes	g. Racing Red/Grey	h. Arctic White/Champagne	
Item no.	SP4044KA	SP4044AA	
UPC	637203048401	637203048364	

Blade Two Meta


Blade Two Meta shares the same Blade DNA in a smaller footprint.



MSRP
€26,000/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex Single apparent source
Drive units	Uni-Q driver array HF: 25 mm (1 in.) aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 4 x 165 mm (6.5 in.) aluminium cone, force cancelling
Frequency response	33 Hz - 35 kHz
Amplifier requirements	50 - 400 W
Sensitivity	86 dB
Maximum output	116 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H1461 x W338 x D475 mm (57.5 x 13.3 x 18.7 in./piece)
Product weight	35.5 kg (77.8 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H1566 x W454 x D622 mm (61.7 x 17.9 x 24.5 in./piece)		
Gross weight	44.6 kg (98.3 lbs./piece)		
Warranty period	5 years		
Finishes	a. Piano Black/Grey	b. Piano Black/Copper	c. Frosted Blue/Blue
Item no.	SP4045BA	SP4045ZA01	SP4045CA
UPC	637203048456	637203048494	637203048463
Finishes	d. Frosted Blue/Bronze	e. Charcoal Grey/Red	f. Charcoal Grey/Bronze
Item no.	SP4044ZA03	SP4045ZA02	SP4045HA
UPC	637203048517	637203048500	637203048470
Finishes	g. Racing Red/Grey	h. Arctic White/Champagne	
Item no.	SP4045KA	SP4045AA	
UPC	637203048487	637203048449	



The Reference

Detail remastered.
An icon redefined for tomorrow.



The essential for any audiophile. Hand built by the masters who set the standard for audio quality, THE REFERENCE has been the benchmark for loudspeakers and sound reproduction. The Reference is an embodiment of KEF's philosophy and the relentless pursuit of perfection. Now with Metamaterial Absorption Technology (MAT™).

Key Features


- Metamaterial Absorption Technology eliminates 99% of high-frequency distortion for pure, natural sound
- Bespoke 12th generation Uni-Q with MAT driver array for exceptional acoustic accuracy
- Enhanced crossover design with fine-tuned signal paths for maximum clarity
- Optimised cabinet design for best acoustic performance
- With mounting inserts to secure on KEF S-RF1 Floor Stand (available as separate item)
- The Reference Series Grille set for each model is available as separate item

Key Technologies

- Uni-Q®
- MAT™

Reference 5 Meta

The flagship model that all other high-performance loudspeakers compare themselves against.



MSRP
€20,000/pair

PRODUCT SPECIFICATION


Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 165 mm (6.5 in.) aluminium cone
Frequency response	40 Hz – 35 kHz (±3 dB)
Amplifier requirements	50 - 400 W
Sensitivity	88 dB
Maximum output	116 dB
Impedance	4Ω (min. 3.2Ω)
Dimensions	H1350 x W205 x H462 mm (53.1 x 8.1 x 18.2 in.)/piece
Product weight	60.2 kg (132.7 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H1555 x W598 x D354 mm (61.2 x 23.5 x 13.9 in.)/piece		
Gross weight	63.9 kg (140.9 lbs.)/piece		
Warranty period	5 years		
Finishes	a. High-gloss white/ Champagne	b. High-gloss white/ Blue	c. High-gloss black/ Grey
Item no.	SP4050AA	SP4050CA	SP4050BA
UPC	637203048685	637203048708	637203048692
Finishes	d. High-gloss black/ Copper	e. Satin Walnut/ Silver	
Item no.	SP4050EA	SP4050WA	
UPC	637203048715	637203048722	

Reference 3 Meta

The floorstanding model that is capable of delivering a sensational sound stage.



MSRP
€13,500/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 2 x 165 mm (6.5 in.) aluminium cone
Frequency response	43 Hz – 35 kHz (±3 dB)
Amplifier requirements	50 - 300 W
Sensitivity	86 dB
Maximum output	113.5 dB
Impedance	4Ω (min. 3.2Ω)
Dimensions	H1155 x W205 x D462 mm (45.5 x 8.1 x 18.2 in.)/piece
Product weight	51.3 kg (113.1 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H1360 x W598 x D354 mm (53.5 x 23.5 x 18.2 in.)/piece		
Gross weight	59.7 kg (131.6 lbs.)/piece		
Warranty period	5 years		
Finishes	a. High-gloss white/ Champagne	b. High-gloss white/ Blue	c. High-gloss black/ Grey
Item no.	SP4049AA	SP4049CA	SP4050BA
UPC	637203048630	637203048654	637203048647
Finishes	d. High-gloss black/ Copper	e. Satin Walnut/ Silver	
Item no.	SP4049EA	SP4049WA	
UPC	637203048661	637203048678	

Reference 1 Meta

The compact standmount model that delivers expansive, high-performance sound beyond what its size suggests.



MSRP
€9,000/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 165 mm (6.5 in.) aluminium cone
Frequency response	45 Hz – 35 kHz (±3 dB)
Amplifier requirements	50 - 200 W
Sensitivity	85 dB
Maximum output	111 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H440 x W205 x D422 mm (17.3 x 8.1 x 16.6 in.)/piece
Product weight	18.2 kg (40.1 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H585 x W598 x D354 mm (23 x 23.5 x 13.9 in.)/piece		
Gross weight	22.8 kg (50.3 lbs.)/piece		
Warranty period	5 years		
Finishes	a. High-gloss white/ Champagne	b. High-gloss white/ Blue	c. High-gloss black/ Grey
Item no.	SP4048AA	SP4048CA	SP4048BA
UPC	637203048586	637203048609	637203048593
Finishes	d. High-gloss black/ Copper	e. Satin Walnut/ Silver	
Item no.	SP4048EA	SP4048WA	
UPC	637203048616	637203048623	

Reference 4 Meta


The flagship centre speaker for movie lovers looking for total immersion.



MSRP
€7,500/piece

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 4 x 165 mm (6.5 in.) aluminium cone
Frequency response	48 Hz – 35 kHz (±3 dB)
Amplifier requirements	50 - 400 W
Sensitivity	88 dB
Maximum output	116 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H205 x W1090 x D463 mm (8.1 x 42.9 x 18.2 in.)/piece
Product weight	45.2 kg (99.6 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H1333 x W598 x D354 mm (52.5 x 23.5 x 13.9 in.)/piece		
Gross weight	53.8 kg (118.6 lbs.)/piece		
Warranty period	5 years		
Finishes	a. High-gloss white/ Champagne	b. High-gloss white/ Blue	c. High-gloss black/ Grey
Item no.	SP4052AA	SP4052CA	SP4052BA
UPC	637203048784	637203048807	637203048791
Finishes	d. High-gloss black/ Copper	e. Satin Walnut/ Silver	
Item no.	SP4052EA	SP4052WA	
UPC	637203048814	637203048821	

Reference 2 Meta


The centre speaker designed for people with smaller rooms but demand high-performance sound.



MSRP
€5,500/piece

PRODUCT SPECIFICATION

Design	Three-way closed box
Drive units	Uni-Q driver array HF: 25 mm (1 in.) aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 2 x 165 mm (6.5 in.) aluminium cone
Frequency response	80 Hz – 35 kHz (±3 dB)
Amplifier requirements	50 - 300 W
Sensitivity	86 dB
Maximum output	113.5 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H205 x W630 x D335 mm (8.1 x 24.8 x 13.2 in.)/piece
Product weight	22.8 kg (50.3 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H760 x W598 x D354 mm (29.9 x 23.5 x 13.9 in.)/piece		
Gross weight	28.4 kg (62.6 lbs.)/piece		
Warranty period	5 years		
Finishes	a. High-gloss white/ Champagne	b. High-gloss white/ Blue	c. High-gloss black/ Grey
Item no.	SP4048AA	SP4051CA	SP4051BA
UPC	637203048586	637203048753	637203048746
Finishes	d. High-gloss black/ Copper	e. Satin Walnut/ Silver	
Item no.	SP4051EA	SP4051WA	
UPC	637203048760	637203048777	

Accessories

Reference 5 Grille Pack*



MSRP
€300/set

PRODUCT SPECIFICATION

Package	Uni-Q grille: 2 pcs LF grille: 8 pcs
----------------	-----------------------------------------

LOGISTIC SPECIFICATION

Packaging dimensions	H223 x W422 x D137 mm (8.8 x 16.6 x 5.4 in.)/set
Gross weight	1.28 kg (2.8 lbs.)/set
Warranty period	2 years
Item no.	SP3882AA
UPC	637203042324

Reference 4c Grille Pack*



MSRP
€180/set

PRODUCT SPECIFICATION


Package	Uni-Q grille: 1 pc LF grille: 4 pcs
----------------	----------------------------------------

LOGISTIC SPECIFICATION

Packaging dimensions	H223 x W422 x D72 mm (8.8 x 16.6 x 2.8 in.)/set
Gross weight	0.7 kg (1.5 lbs.)/set
Warranty period	2 years
Item no.	SP3883AA
UPC	637203042331



Reference 3 Grille Pack*



MSRP
€250/set

PRODUCT SPECIFICATION

Package Uni-Q grille: 2 pcs
LF grille: 4 pcs

LOGISTIC SPECIFICATION

Packaging dimensions	H223 x W422 x D72 mm (8.8 x 16.6 x 2.8 in.)/set
Gross weight	0.73 kg (1.6 lbs.)/set
Warranty period	2 years
Item no.	SP3881AA
UPC	637203042317

Reference 2 Grille Pack*



MSRP
€100/set

PRODUCT SPECIFICATION

Package Uni-Q grille: 1 pc
LF grille: 2 pcs

LOGISTIC SPECIFICATION

Packaging dimensions	H223 x W422 x D47 mm (8.8 x 16.6 x 1.9 in.)/set
Gross weight	0.46 kg (1 lbs.)/set
Warranty period	2 years
Item no.	SP3887AA
UPC	637203042348

Reference 1 Grille Pack*



MSRP
€130/set

PRODUCT SPECIFICATION

Package Uni-Q grille: 2 pcs
LF grille: 2 pcs

LOGISTIC SPECIFICATION

Packaging dimensions	H223 x W422 x D47 mm (8.8 x 16.6 x 1.9 in.)/set
Gross weight	0.5 kg (1.1 lbs.)/set
Warranty period	2 years
Item no.	SP3880AA
UPC	637203042300

S-RF1 Floor Stand*




MSRP
€1,200/pair

PRODUCT SPECIFICATION

Dimensions H542 x W260 x D387 mm
(21.4 x 10.2 x 15.2 in.)/stand

Product weight 7.95 kg (17.5 lbs.)/stand

Compatible models Reference 1 meta



LOGISTIC SPECIFICATION

Packaging dimensions	H229 x W730 x D600 mm (8.7 x 28.7 x 23.6 in.)/set	
Gross weight	19.9 kg (43.9 lbs.)/set	
Warranty period	2 years	
Finishes	a. Carbon Black	b. Mineral White
Item no.	SP4061BA	SP4061AA
UPC	637203048999	637203049002



R Series

Performance redefined.
An icon born from The Reference.



Developed for KEF's flagship The Reference, a suite of the latest technologies has now made its way into the new generation of the R Series. Whether in stereo for music or in a home theatre set up the R Series makes exceptional acoustic performance more accessible. Now with the groundbreaking Metamaterial Absorption Technology, the R Series reveals exquisite detail and incredible insight: truly an experience to savour.

Key Features

- Metamaterial Absorption Technology (MAT™) eliminates 99% of high-frequency distortion for pure, natural sound
- Bespoke 12th generation Uni-Q with MAT driver array for exceptional acoustic accuracy
- Refined tweeter gap damper tames resonances for improved detail
- Flexible Decoupling Chassis prevents unwanted vibrations for better clarity
- Enhanced crossover design with fine-tuned signal paths for maximum clarity
- Microfibre grilles offer the perfect balance between driver protection, sonic performance and aesthetics

Key Technologies

- Uni-Q®
- MAT™

R11 Meta


Flagship three-way floorstanding speakers



MSRP
€6,500/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 4 x 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	46 Hz - 28 kHz (±3 dB)
Amplifier requirements	15 - 300 W
Sensitivity	90 dB
Maximum output	113 dB
Impedance	4 Ω (min. 32 Ω)
Dimensions	H1296 x W311 x D384 mm (51.0 x 12.2 x 15.1 in./piece)
Product weight	36.5 kg (80.5 lbs)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H1447 x W512 x D346 mm (57 x 20.2 x 13.6 in./piece)		
Gross weight	43.5 kg (95.9 lbs./piece)		
Warranty period	5 years		
Finishes	a. Black Gloss	b. White Gloss	c. Walnut
Item no.	SP4056B1AA	SP4056A1AA	SP4056W0AA
UPC	637203049774	637203049781	637203049798

R7 Meta


Mid-sized three-way floorstanding speakers



MSRP
€5,000/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 2 x 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	48 Hz - 28 kHz (±3 dB)
Amplifier requirements	15 - 250 W
Sensitivity	88 dB
Maximum output	111 dB
Impedance	4 Ω (min. 32 Ω)
Dimensions	H1109 x W311 x D384 mm (43.7 x 12.2 x 15.1 in./piece)
Product weight	29.3 kg (64.6 lbs)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H1261 x W512 x D346 mm (49.6 x 20.2 x 13.6 in./piece)		
Gross weight	35.8 kg (78.9 lbs./piece)		
Warranty period	5 years		
Finishes	a. Black Gloss	b. White Gloss	c. Walnut
Item no.	SP4055B1AA	SP4055A1AA	SP4055W0AA
UPC	637203049736	637203049743	637203049750
Finishes	d. Titanium Gloss Special Edition		
Item no.	SP4055H1AA		
UPC	637203049767		

R5 Meta


Compact three-way floorstanding speakers



MSRP
€3,500/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 2 x 130 mm (5.25 in.) hybrid aluminium cone
Frequency response	52 Hz - 28 kHz (±3 dB)
Amplifier requirements	15 - 200 W
Sensitivity	87 dB
Maximum output	110 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H1072 x W272 x D344 mm (42.2 x 10.7 x 13.5 in.)/piece
Product weight	24.5 kg (54 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H1223 x W472 x D321 mm (48.1 x 18.6 x 12.6 in.)/piece		
Gross weight	31.4 kg (69.2 lbs.)/piece		
Warranty period	5 years		
Finishes	a. Black Gloss	b. White Gloss	c. Walnut
Item no.	SP4054B1AA	SP4054A1AA	SP4054W0AA
UPC	637203049705	637203049712	637203049729

R3 Meta


Three-way bookshelf speaker



MSRP
€2,200/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	58 Hz - 28 kHz (±3 dB)
Amplifier requirements	15 - 180 W
Sensitivity	87 dB
Maximum output	110 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H422 x W200 x D336 mm (16.6 x 7.9 x 13.2 in.)/piece
Product weight	12.4 kg (27.3 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H1261 x W512 x D346 mm (49.6 x 20.2 x 13.6 in.)/pair		
Gross weight	35.8 kg (78.9 lbs.)/pair		
Warranty period	5 years		
Finishes	a. Black Gloss	b. White Gloss	c. Walnut
Item no.	SP4053B1AA	SP4053A1AA	SP4053W0AA
UPC	637203049668	637203049675	637203049682
Finishes	d. Indigo Gloss Special Edition		
Item no.	SP4053C1AA		
UPC	637203049699		

R6 Meta


Flagship three-way centre channel speaker



MSRP
€1,800/piece

PRODUCT SPECIFICATION

Design	Three-way closed box
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 2 x 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	65 Hz - 28 kHz (±3 dB)
Amplifier requirements	15 - 250 W
Sensitivity	88 dB
Maximum output	111 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H200 x W625 x D339 mm (7.9 x 24.6 x 13.3 in.)/piece
Product weight	17.8 kg (39.2 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H336 x W769 x D456 mm (13.2 x 30.3 x 18 in.)/piece		
Gross weight	21.4 kg (47.2 lbs.)/piece		
Warranty period	5 years		
Finishes	a. Black Gloss	b. White Gloss	c. Walnut
Item no.	SP4058B1AA	SP4058A1AA	SP4058W0AA
UPC	637203049835	637203049842	637203049859

R2 Meta


Compact three-way centre channel speaker



MSRP
€1,400/piece

PRODUCT SPECIFICATION

Design	Three-way closed box
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5 in.) aluminium cone Bass units LF: 2 x 130 mm (5.25 in.) hybrid aluminium cone
Frequency response	67 Hz - 28 kHz (±3 dB)
Amplifier requirements	15 - 200 W
Sensitivity	87 dB
Maximum output	110 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H175 x W550 x D309 mm (6.9 x 21.7 x 12.2 in.)/piece
Product weight	15.4 kg (34.0 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H311 x W682 x D432 mm (12.2 x 26.9 x 17 in.)/piece		
Gross weight	18.1 kg (40 lbs.)/piece		
Warranty period	5 years		
Finishes	a. Black Gloss	b. White Gloss	c. Walnut
Item no.	SP4057B1AA	SP4057A1AA	SP4057W0AA
UPC	637203049804	637203049811	637203049828



R8 Meta


Dolby Atmos surround speakers



MSRP
€1,600/pair

PRODUCT SPECIFICATION

Design	Two-way closed box
Drive units	Uni-Q driver array HF: 5 mm (1 in.) vented aluminium dome with MAT MF/ LF: 130 mm (5.25 in.) aluminium cone
Frequency response	97 Hz - 17.5 kHz (±3 dB)
Amplifier requirements	25 - 150 W
Sensitivity	85 dB
Maximum output	106 dB
Impedance	4Ω (min. 3.2 Ω)
Dimensions	H174 x W175 x D259 mm (6.9 x 6.9 x 10.2 in./piece)
Product weight	4.5 kg (9.9 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H301 x W467 x D388 mm (11.9 x 18.4 x 15.3 in./pair)		
Gross weight	11.4 kg (25.1 lbs./pair)		
Warranty period	5 years		
Finishes	a. Black Gloss	b. White Gloss	c. Walnut
Item no.	SP4059BA	SP4059AA	SP4059WA
UPC	637203218620	637203218637	637203218736

Accessories

S3 Floor Stand*


Speaker stand for R3 Meta



MSRP
€699/pair

PRODUCT SPECIFICATION

Dimensions	H542 x W260 x D387 mm (21.4 x 10.2 x 15.2 in./stand)
Product weight	6.7 kg (14.7 lbs./stand)



LOGISTIC SPECIFICATION

Packaging dimensions	H205 x W730 x D600 mm (8.1 x 28.7 x 23.6 in./pair)		
Gross weight	17.4 kg (38.4 lbs./pair)		
Warranty period	2 years		
Finishes	a. Slate Grey	b. Mineral White	c. Indigo Matte Special Edition
Item no.	SP4062MA	SP4062AA	SP4062CA
UPC	637203049019	637203049026	637203049866

*Fits both R3 and R3 Meta models



Q Series

The Q Series with MAT™ always has the sound solution for you



The 9th iteration of the Q Series is upgraded with Metamaterial Absorption Technology (MAT™). From compact bookshelf speakers and slender on-wall speaker to powerful floorstanding and home cinema models, the new Q Series fits any room, any budget - perfect for music, TV, movies, and gaming. Now impeccable, high-fidelity sound is more accessible than ever.

Key Features

- Metamaterial Absorption Technology (MAT™) eliminates 99% of high-frequency distortion for pure, natural sound
- 12th generation Uni-Q with MAT driver array for exceptional acoustic accuracy
- Enhanced crossover design with fine-tuned signal paths for pristine, clean sound
- Three-way design for enhanced clarity and detail (Q11 Meta, Q7 Meta, Q Concerto Meta, Q6 Meta)
- Hybrid aluminium cone LF driver for deep and powerful bass (Q11 Meta, Q7 Meta, Q Concerto Meta, Q6 Meta)
- Magnetic grilles offer the perfect balance between driver protection and aesthetics

Key Technologies

- Uni-Q®
- MAT™

Q11 Meta


Flagship 3-way floorstanding speaker



MSRP
€2,198/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) vented aluminium dome with MAT MF: 100 mm (4 in.) aluminium cone Bass units 3 x 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	44 Hz - 20 kHz (±3 dB)
Amplifier requirements	15 - 225W
Sensitivity	89 dB
Maximum output	113 dB
Impedance	4Ω (min. 3.2 Ω)
Dimensions	H1112 x W317 x D380 mm (43.8 x 12.5 x 15.0 in./piece)
Product weight	22.5 kg (49.6 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H1211 x W500 x D349 mm (47.7 x 19.7 x 13.7 in./piece)		
Gross weight	28.9 kg (63.7 lbs./piece)		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4093B0AA / SP4093B0A1	SP4093A0AA / SP4093A0A1	SP4093W0AA / SP4093W0A1
UPC	637203219016	637203219009	637203218996

Q7 Meta


3-way floorstanding speaker



MSRP
€1,598/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) vented aluminium dome with MAT MF: 100 mm (4 in.) aluminium cone Bass units 2 x 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	46 Hz - 20 kHz (±3 dB)
Amplifier requirements	15 - 200W
Sensitivity	87 dB
Maximum output	110 dB
Impedance	4Ω (min. 3.2 Ω)
Dimensions	H1001 x W317 x D315 mm (39.4 x 12.5 x 12.4 in./piece)
Product weight	18.4 kg (40.6 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H1099 x W433 x D349 mm (43.3 x 17.0 x 13.7 in./piece)		
Gross weight	24.2 kg (53.4 lbs./piece)		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4092B0AA / SP4092B0A1	SP4092A0AA / SP4092A0A1	SP4092W0AA / SP4092W0A1
UPC	637203219047	637203219030	637203219023

Q Concerto Meta


3-way bookshelf speaker



MSRP
€1,198/pair

PRODUCT SPECIFICATION

Design	Three-way bass reflex
Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) vented aluminium dome with MAT MF: 100 mm (4 in.) aluminium cone Bass units 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	48 Hz - 20 kHz (±3 dB)
Amplifier requirements	15-180W
Sensitivity	85 dB
Maximum output	108 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H415 x W210 x D315 mm (16.3 x 8.3 x 12.4 in./piece)
Product weight	9.5 kg (20.9 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H549 x W600 XD440 mm (21.6 x 23.6 x 17.3 in./pair)		
Gross weight	22.1 kg (48.7 lbs)/pair		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4090B0AA/ SP4090B0A1	SP4090A0AA/ SP4090A0A1	SP4090W0AA/ SP4090W0A1
UPC	637203219108	637203219092	637203219085

Q3 Meta


2-way bookshelf speaker



MSRP
€698/pair

PRODUCT SPECIFICATION

Design	Two-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT LF/MF: 165 mm (6.5 in.) aluminium cone
Frequency response	49 Hz - 20 kHz (±3 dB)
Amplifier requirements	15-150W
Sensitivity	87 dB
Maximum output	109 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H357 x W210 x D305 mm (14.1 x 8.3 x 12.0 in./piece)
Product weight	8.2 kg (18.1 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H492 x W600 XD430 mm (19.4 x 23.6 x 16.9 in./pair)		
Gross weight	19.5 kg (43.0 lbs)/pair		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4089B0AA/ SP4089B0A1	SP4089A0AA/ SP4089A0A1	SP4089W0AA/ SP4089W0A1
UPC	637203219139	637203219122	637203219115

Q1 Meta


2-way bookshelf speaker



MSRP
€499/pair

PRODUCT SPECIFICATION

Design	Two-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT LF/MF: 130 mm (5.25 in.) aluminium cone
Frequency response	51 Hz - 20 kHz (±3 dB)
Amplifier requirements	10-150W
Sensitivity	86 dB
Maximum output	108 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H302 x W180 x D277 mm (11.9 x 7.1 x 10.9 in./piece)
Product weight	6.1 kg (13.4 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H438 x W539 XD399 mm (17.2 x 21.2x 15.7in./pair)		
Gross weight	14.8 kg (32.6 lbs)/pair		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4087B0AA/ SP4087B0A1	SP4087A0AA/ SP4087A0A1	SP4087W0AA/ SP4087W0A1
UPC	637203219160	637203219153	637203219146

Q4 Meta


2-way on-wall speaker



MSRP
€349/piece

PRODUCT SPECIFICATION

Design	Two-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium domewith MAT MF/LF: 130 mm (5.25 in.) aluminium cone
Frequency response	65 Hz - 20 kHz (±3 dB)
Amplifier requirements	10-150W
Sensitivity	86 dB
Maximum output	108 dB
Impedance	4 Ω (min. 3.2 Ω)
Dimensions	H400 x W250 x D142 mm (15.7 x 9.8 x 5.6 in./piece)
Product weight	5.7 kg (12.6 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H500 x W352 XD231 mm (19.7 x 13.9 x 9.1in./piece)		
Gross weight	6.9 kg (15.2 lbs)/piece		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4088B0AA/ SP4088B0A1	SP4088A0AA/ SP4088A0A1	SP4088W0AA/ SP4088W0A1
UPC	637203219177	637203219164	637203219191

Q6 Meta


3-way centre channel speaker



MSRP
€749/piece

PRODUCT SPECIFICATION

Design	Three-way closed box
Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) vented aluminium dome with MAT MF: 100 mm (4 in.) aluminium cone Bass units 2 x 165 mm (6.5 in.) hybrid aluminium cone
Frequency response	63 Hz - 20 kHz (±3 dB)
Amplifier requirements	15-200W
Sensitivity	86 dB
Maximum output	109 dB
Impedance	4Ω (min. 3.2 Ω)
Dimensions	H210 x W629 x D303 mm (8.3 x 24.8 x 11.9 in.)/piece
Product weight	14.1 kg (31.1 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H361 x W756 x D439 mm (14.2 x 29.8 x 17.3 in.)/piece		
Gross weight	16.8 kg (37.0 lbs)/piece		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4091B0AA/ SP4091B0A1	SP4091A0AA/ SP4091A0A1	SP4091W0AA/ SP4091W0A1
UPC	637203219078	637203219061	637203219054

Q8 Meta


Dolby Atmos surround speaker



MSRP
€698/pair

PRODUCT SPECIFICATION

Design	Two-way closed box
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF/LF: 130 mm (5.25 in.) aluminium cone
Frequency response	105 Hz - 20 kHz (±3 dB)
Amplifier requirements	10-150W
Sensitivity	86 dB
Maximum output	109 dB
Impedance	4Ω (min. 3.2 Ω)
Dimensions	H176 x W180 x D259 mm (6.9 x 7.1 x 10.2 in.)/piece
Product weight	4.5 kg (9.9 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H286 x W473 x D382 mm (11.3 x 18.6 x 15.0 in.)/pair		
Gross weight	10.7 kg (23.6 lbs)/pair		
Warranty period	5 years		
Finishes	a. Satin Black	b. Satin White	c. Walnut
Item no.	SP4094B0AA/ SP4094B0A1	SP4094A0AA/ SP4094A0A1	SP4094W0AA/ SP4094W0A1
UPC	637203218989	637203218972	637203218965

Accessories

SQ1 Floor Stand


Speaker stand for Q Series bookshelf speakers



MSRP
€299/pair

PRODUCT SPECIFICATION

Dimensions	H615 x W260 x D350 mm (24.2 x 10.2 x 13.8 in.)/piece
Product weight	3.25 kg (7.2 lbs.) per stand



LOGISTIC SPECIFICATION

Packaging dimensions	H155 x W625 x D435mm (6.1 x 24.6 x 17.1 in.)/pair	
Gross weight	8.4 kg (18.5 lbs)/pair	
Warranty period	2 years	
Finishes	a. Mineral White	b. Slate Grey
Item no.	SP4107A0AA	SP4107M0AA
UPC	637203050992	637203051005

B2 Wall Bracket



MSRP
€49/pair

PRODUCT SPECIFICATION

Dimensions	Bracket: H39 x W148 x D28 mm (1.5 x 5.8 x 1.1 in.)/piece Rubber: H20 x W60 x D26 mm (0.8 x 2.4 x 1 in.)/piece
Product weight	Bracket: 0.33 kg (0.7 lbs.)/piece Rubber: 32 g/piece
Compatible models	Q3 Meta, Q1 Meta

LOGISTIC SPECIFICATION

Packaging dimensions	H56 x W225 x D150 mm (2.2 x 8.9 x 5.9 in.)/set	
Gross weight	0.55 kg (1.2 lbs.)/set	
Warranty period	2 years	
Item no.	SP3980BA	
UPC	637203044656	

PQ1 Plinth Spike Set



MSRP
€85/set

PRODUCT SPECIFICATION

Product weight	386 g (0.85 lb) per set
-----------------------	-------------------------

LOGISTIC SPECIFICATION

Packaging dimensions	H36 x W252 x D157mm (1.4 x 9.9 x 6.2 in.)/set	
Gross weight	0.47 kg (1.0 lbs)/set	
Warranty period	2 years	
Item no.	SP4106B0AA	
UPC	637203050985	



LS50 Meta

The World's First Speakers with Metamaterial



LS50 Meta is a highly precise, emotionally engaging loudspeaker built on revolutionary acoustic technology. Designed around the Uni-Q 12th Generation with Metamaterial Absorption Technology driver array, this solid, compact loudspeaker is capable of delivering detailed sound anywhere in the room.

Key Features

- Metamaterial Absorption Technology eliminates 99% of high-frequency distortion for pure, natural sound
- 12th generation Uni-Q with MAT™ driver array for exceptional acoustic accuracy
- Driver Performance Optimisation for enhanced sonic performance, less distortion and reduced coloration
- Patented off-set flexible port for reduced midrange coloration with exceptional levels of depth and detail

Key Technologies

- Uni-Q®
- MAT™

LS50 Meta


The World's First Speakers with Metamaterial



MSRP
€1,299/pair

PRODUCT SPECIFICATION

Design	Two-way bass reflex
Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF/LF: 130 mm (5.25 in.) aluminium cone
Frequency response	9 Hz -28 kHz (±3 dB)
Amplifier requirements	40-100 W
Sensitivity	85 dB
Maximum output	106 dB
Impedance	8 Ω (min. 3.5 Ω)
Dimensions	H302 x 200 x 280.5 mm (11.9 x 7.9 x 11.0 in.)/piece
Product weight	7.8 kg (17.2 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H407 x W565 x D368 mm (16 x 22.2 x 14.5 in.)/pair		
Gross weight	17.8 kg (39.2 lbs.)/pair		
Warranty period	5 years		
Finishes	a. Carbon Black	b. Titanium Grey	c. Mineral White
Item no.	SP4027BA	SP4027HA	SP4027AA
UPC	637203217791	637203217821	637203217906
Finishes	d. Royal Blue Special Edition		
Item no.	SP4027CA		
UPC	637203217869		



T Series

Slim Speakers, Serious Sound



As one of the world's thinnest high performance home theatre systems, the T Series combines several landmark innovations: a radical ultra-low profile bass and midrange driver, and a large, fully vented tweeter. By incorporating both in cabinets only 35mm (just over 1.25in.) deep, the T Series brings you all the pleasures of true audiophile quality sound in a speaker that perfectly complements the aesthetics of the latest flat screen TVs.

Key Features

- Exceptionally slim profile speakers that generate all the detail, spaciousness and dynamics of a high-end conventional design
- Ultra-slim bass driver that allows the enclosure to be as slim as a flat screen TV without compromising acoustic integrity
- Vented tweeter allows exceptional accuracy of reproduction, especially of the voice

T301 Satellite Speakers

Slim profile full-sized satellite speakers



MSRP
€600/pair

PRODUCT SPECIFICATION

Design	Two and a half-way closed box
Drive units	HF: 25 mm (1 in.) aluminium MF: 2 x 115 mm (4.5 in.) dual layer
Frequency response	80 Hz - 30 kHz (±3dB)
Amplifier requirements	10-150 W
Sensitivity	91dB (wall mount) 88dB (floor stand mount)
Maximum output	110 dB
Impedance	8 Ω
Dimensions	H600 x W140 x D35 mm (23.6 x 5.5 x 1.4 in.)/piece
Product weight	1.5 kg (3.3 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H220 x W667 x D265 mm (8.7 x 26.3 x 10.4 in.)/pair	
Gross weight	6.8 kg (15 lbs.)/pair	
Warranty period	5 years	
Finishes	a. Black	b. White
Item no.	SP3745BB	SP3745AA
UPC	637203207785	637203210341

T101 Satellite Speakers

Slim profile compact satellite speakers



MSRP
€458/pair

PRODUCT SPECIFICATION

Design	Two-way closed box
Drive units	HF: 25 mm (1 in.) aluminium MF: 115 mm (4.5 in.) dual layer
Frequency response	80 Hz - 30 kHz (±3 dB)
Amplifier requirements	10-100 W
Sensitivity	90 dB (wall mount) 87 dB (floor stand mount)
Maximum output	107 dB
Impedance	8 Ω
Dimensions	H330 x W140 x D35 mm (13.0 x 5.5 x 1.4 in.)/piece
Product weight	1 kg (2.2 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H220 x W416 x D245 mm (8.7 x 16.4 x 9.6 in.)/pair	
Gross weight	4.5 kg (9.9 lbs.)/pair	
Warranty period	5 years	
Finishes	a. Black	b. White
Item no.	SP3744BB	SP3744AA
UPC	637203207792	637203210327

T301c Centre Channel Speaker


Two and a half-way centre channel

	
MSRP €319/piece	
PRODUCT SPECIFICATION	
Design	Two and a half-way closed box
Drive units	HF: 25 mm (1 in.) aluminium MF: 2 x 115 mm (4.5 in.) dual layer
Frequency response	80 Hz - 30 kHz (±3 dB)
Amplifier requirements	10 - 150 W
Sensitivity	91 dB (wall mount) 88 dB (floor stand mount)
Maximum output	110 dB
Impedance	8 Ω
Dimensions	H140 x W600 x D35 mm (5.5 x 23.6 x 1.4 in.)/piece
Product weight	1.5 kg (3.3 lbs.)/piece
LOGISTIC SPECIFICATION	
Packaging dimensions	H234 x W667 x D130 mm (9.2 x 26.3 x 5.1 in.)/piece
Gross weight	3.5 kg (7.7 lbs.)/piece
Warranty period	5 years
Finishes	a. Black b. White
Item no.	SP3747BB SP3747AA
UPC	637203207761 637203210358



T101c Centre Channel Speaker

Two half-way centre channel

	
MSRP €240/piece	
PRODUCT SPECIFICATION	
Design	Two-way closed box
Drive units	HF: 25 mm (1 in.) aluminium MF: 115 mm (4.5 in.) dual layer
Frequency response	80 Hz - 30 kHz (±3 dB)
Amplifier requirements	10 - 100 W
Sensitivity	90 dB (wall mount) 87 dB (floor stand mount)
Maximum output	107 dB
Impedance	8 Ω
Dimensions	H140 x W330 x D35 mm (5.5 x 13.0 x 1.4 in.)/piece
Product weight	1 kg (2.2 lbs.)/piece
LOGISTIC SPECIFICATION	
Packaging dimensions	H234 x W397 x D130 mm (9.2 x 15.6 x 5.1 in.)/piece
Gross weight	2.2 kg (4.9 lbs.)/piece
Warranty period	5 years
Finishes	a. Black b. White
Item no.	SP3746BB SP3746AA
UPC	637203207778 637203210334



Systems

T305 Home Theatre Speaker System

Slim profile full-sized
5.1 Home Theatre System



MSRP
€n.a./system

PRODUCT SPECIFICATION

4 x T301
1 x T301c
1 x T2 subwoofer

T205 Home Theatre Speaker System

Slim profile mid-sized
5.1 Home Theatre System



MSRP
€n.a./system

PRODUCT SPECIFICATION

2 x T301
2 x T101
1 x T301c
1 x T2 subwoofer

T105 Home Theatre Speaker System

Slim profile compact
5.1 Home Theatre System



MSRP
€n.a./system

PRODUCT SPECIFICATION

4 x T101
1 x T101c
1 x T2 subwoofer

Accessories

T Series Floor Stand

This elegantly simple floor stand matches T Series satellites



MSRP
€358/pair

PRODUCT SPECIFICATION

Dimensions H870 mm x W250 mm (34 in. x 9.8 in.)/stand
Product weight 2.96 kg (6.5 lbs.)/stand

LOGISTIC SPECIFICATION

Packaging dimensions H85 x W980 x D310 mm (3.3 x 38.6 x 12.2 in.)/pair
Gross weight 7.16 kg (15.8 lbs.)/pair
Warranty period 2 years
Finishes a. Black b. Silver
Item no. SP3748BB SP3748AA
UPC 637203207914 637203211003

Wireless HiFi Speakers & Accessories



LS Wireless Collection

Immersion engines



KEF's engineers and designers have always been looking and listening ahead. The LS Wireless Collection is the sound of the future, bringing breakthrough technology including Uni-Q, Uni-Core, Metamaterial Absorption Technology (MAT) and Music Integrity Engine (MIE), into the home in a series of all-in-one, plug and play speaker systems. Each of the four models – LS60 Wireless, LS50 Wireless II, LSX II and LSX II LT – are specially developed to deliver room-filling, immersive sound experience for music, TV, movies and gaming. Stream High-Fidelity sound in its truest form, from any source, every time.

LS60 Wireless

The immersion engine



MSRP
€4,999/system

PRODUCT DESCRIPTION

Key technologies Uni-Q, MAT, Uni-core, SAS, MIE

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) vented aluminium dome with MAT MF: 100 mm (4in.) aluminium cone Uni-Core Force Cancelling Driver LF: 4 x 135 mm (5.25 in.)
Frequency response	31 Hz - 24 kHz (±3 dB)
Amplifier power (per speaker)	HF: 100 W, MF: 100 W, LF: 500 W
Amplifier class (per speaker)	HF: Class AB, MF: Class D, LF: Class D
MAX SPL	111 dB (measured at 1 m)
Inputs	HDMI eARC, TOSLINK Optical, Digital Coaxial, Analog RCA, USB Type A (service), RJ45 Ethernet (network), RJ45 Ethernet (interspeaker)
Output	RCA Subwoofer output
Dimensions	H1090 x W212 x D394 mm (42.9 x 8.3 x 15.5 in.)/piece
Product weight	62.4 kg (138 lbs.)/set



LOGISTIC SPECIFICATION

Packaging dimensions	H1260 x W520 x D310 mm (49.6 x 20.5 x 12.2 in.)/piece		
Gross weight	39 kg (86 lbs.)/piece		
Warranty period	2 years electronics, 5 years drivers		
Finishes	a. Carbon Black	b. Titanium Grey	c. Royal Blue
Item no.	SP4017BB	SP4017HB	SP4017CB
UPC	637203050138	637203048203	637203048180
Finishes	d. Mineral White		
Item no.	SP4017AB		
UPC	637203048197		

LS50 Wireless II

The Ultimate Wireless HiFi Speakers




MSRP
€2,299/system

PRODUCT DESCRIPTION

Key technologies Uni-Q, MAT, MIE

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT LF: 130 mm (5.25 in.) aluminium cone
Frequency response	45 Hz - 28 kHz (±3 dB)
Amplifier power (per speaker)	HF: 100 W, LF: 280 W
Amplifier class (per speaker)	HF: Class AB, MF: Class D, LF: Class D
MAX SPL	108 dB (measured at 1 m)
Inputs	Primary speaker HDMI eARC, TOSLINK Optical, Digital Coaxial, Analog 3.5mm Auxiliary, USB Type A (service), RJ45 Ethernet (network), RJ45 Ethernet (interspeaker) Secondary speaker USB Type A (service), RJ45 Ethernet (interspeaker)
Output	RCA Subwoofer output
Dimensions	H305 x W200 x D311 mm (12.0 x 7.9 x 12.2 in.)/piece
Product weight	20.1 kg (44.31 lbs.)/set



LOGISTIC SPECIFICATION

Packaging dimensions	H405 x W595 x D415 mm (15.9 x 23.4 x 16.3 in.)/pair		
Gross weight	23.5 kg (51.8 lbs.)/pair		
Warranty period	2 years electronics, 5 years drivers		
Finishes	a. Carbon Black	b. Titanium Grey	c. Mineral White
Item no.	SP4025BB	SP4025HB	SP4025AB
UPC	637203046926	637203046940	637203046933
Finishes	d. Crimson Red Special Edition		
Item no.	SP4025KB		
UPC	637203046957		

LSX II

The Definitive Compact Wireless HiFi



MSRP
€1,399/system

PRODUCT DESCRIPTION

Key technologies Uni-Q, MIE

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) vented aluminium dome with MAT MF: 100 mm (4 in.) aluminium cone Uni-Core Force Cancelling Driver LF: 4 x 135 mm (5.25 in.)
Frequency response	54 Hz – 28 kHz (±3 dB)
Amplifier power (per speaker)	HF: 30W, LF: 70W
Amplifier class (per speaker)	HF: Class D, LF: Class D
MAX SPL	102 dB (measured at 1m)
Inputs	Primary speaker HDMI ARC, TOSLINK Optical, USB Type C, Analog 3.5mm Auxiliary, RJ45 Ethernet (network), RJ45 Ethernet (interspeaker) Secondary speaker RJ45 Ethernet (interspeaker)
Output	RCA Subwoofer output
Dimensions	H240 x W155 x D180 mm (9.5 x 6.1 x 7.1 in.)/piece
Product weight	7.2 kg (15.6 lbs.)/pair



LOGISTIC SPECIFICATION

Packaging dimensions	H355 x W430 x D250 mm (14 x 16.9 x 9.8 in.)/pair		
Gross weight	10 kg (22 lbs.)/pair		
Warranty period	2 years electronics, 5 years drivers		
Finishes	a. Carbon Black	b. Mineral White	c. Cobalt Blue
Item no.	SP4041BB	SP4041AB	SP4041CB
UPC	637203047817	637203047824	637203047800
Finishes	d. Lava Red e. Soundwave by Terencef, Olive Green Conran		
Item no.	SP4041KB	SP4041DB	SP4041JB
UPC	637203047794	637203047831	637203047848

LSX II LT

The new addition to the award-winning LSX family




MSRP
€999/system

PRODUCT DESCRIPTION

Key technologies Uni-Q, MIE

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) aluminium dome LF/MF: 115 mm (4.5 in.) magnesium/aluminium alloy cone
Frequency response	54 Hz – 28 kHz (±3 dB)
Amplifier power (per speaker)	HF: 30 W, LF: 70 W
Amplifier class (per speaker)	HF: Class D, LF: Class D
MAX SPL	102 dB (measured at 1m)
Inputs	Primary speaker HDMI ARC, TOSLINK Optical, USB Type C, USB Type C (interspeaker), RJ45 Ethernet (network) Secondary speaker USB Type C (interspeaker)
Output	RCA Subwoofer output
Dimensions	H240 x W155 x D180 mm (9.5 x 6.1 x 7.1 in.)/piece
Product weight	6.8 kg (15 lbs.)/pair



LOGISTIC SPECIFICATION

Packaging dimensions	H320 x W475 x D255 mm (12.6 x 18.7 x 10 in.)/pair		
Gross weight	9 kg (19.8 lbs.)/pair		
Warranty period	2 years electronics, 5 years drivers		
Finishes	a. Graphite Grey	b. Stone White	c. Sage Green
Item no.	SP4077M2BA	SP4077A2BA	SP4077J2BA
UPC	637203050626	637203050480	637203050558

Accessories

S2 Floor Stand


Stands that deliver



MSRP
€450/pair

PRODUCT SPECIFICATION

Dimensions	H657 x W226 x D308 mm (25.9 x 8.9 x 12.1 in.)/stand
Product weight	4.85 kg (10.7 lbs.)/stand
Compatible models	LS50 Wireless II, LS50 Meta



LOGISTIC SPECIFICATION

Packaging dimensions	H140 x W680 x D380 mm (5.5 x 26.8 x 15 in.)/pair		
Gross weight	11 kg (24.3 lbs.)/pair		
Warranty period	2 years		
Finishes	a. Carbon Black	b. Titanium Grey	c. Mineral White
Item no.	SP4030BA	SP4030HA	SP4030AA
UPC	637203046735	637203046759	637203046742
Finishes	d. Royal Blue Special Edition e. Crimson Red Special Edition		
Item no.	SP4030CA	SP4030KA	
UPC	637203046780	637203046797	

*Fits both LS50 Meta and LS50 Wireless II

S1 Floor Stand


Speaker stand for LSX II & LSX II LT



MSRP
€349/pair

PRODUCT SPECIFICATION

Dimensions	H683 x W208 x D251 mm (26.9 x 8.2 x 9.9 in.)/stand
Product weight	2.93 kg (6.5 lbs.)/stand
Compatible models	LSX II, LSX II LT



LOGISTIC SPECIFICATION

Packaging dimensions	H144 x W731 x D341 mm (5.7 x 28.8 x 13.4 in.)/pair		
Gross weight	7.4 kg (16.3 lbs.)/pair		
Warranty period	2 years		
Finishes	a. Cobalt Blue	b. Slate Grey	c. Crimson Red
Item no.	SP4030BA	SP4030HA	SP4030AA
UPC	637203046735	637203046759	637203046742
Finishes	d. Mineral White		
Item no.	SP4030CA		
UPC	637203046780		

P1 Desk Pad

Desk Pad designed for LSX II and LSX II LT




MSRP
€140/pair

PRODUCT SPECIFICATION

Dimensions H27.5 x W146.7 x D167.5 mm
(25.9 x 8.9 x 12.1 in./piece)

Compatible models LSX II, LSX II LT



LOGISTIC SPECIFICATION

Packaging dimensions H102 x W221 x D204 mm (4 x 8.7 x 8 in.)/pair

Gross weight 1.5 kg (3.3 lbs.)/pair

Warranty period 2 years

Finishes a. Black b. Silver

Item no. SP4013BA SP4013GA

UPC 637203046025 637203046032

B1 Wall Bracket

Wall mount bracket for LSX II




MSRP
€190/pair

PRODUCT SPECIFICATION

Dimensions H169 x W146.7 x D208.7 mm
(6.7 x 5.8 x 8.2 in.)/piece

Compatible models LSX II



LOGISTIC SPECIFICATION

Packaging dimensions H123 x W304 x D224 mm (4.8 x 12 x 8.8 in.)/pair

Gross weight 1.45 kg (3.2 lbs.)/pair

Warranty period 2 years

Finishes a. Black b. Silver

Item no. SP4015BA SP4015GA

UPC 637203046070 637203046063

K-Stream

Interspeaker cable



MSRP
€159/piece

PRODUCT SPECIFICATION

Standard Category 6A cable (Cat 6A)

Length 8 metres

Compatible models LS60 Wireless, LS50 Wireless II, LSX II



LOGISTIC SPECIFICATION

Packaging dimensions H230 x W230 x D60 mm (9.1 x 9.1 x 2.4 in.)/piece

Gross weight 0.5 kg (1.1 lbs.)/piece

Warranty period 2 years

Finishes a. White with Copper b. Titanium with Copper

Item no. SP4063AX SP4063HX

UPC 637203049095 637203049101

C-Link Interspeaker Cable

Interspeaker cable for LSX II LT



MSRP
€59/piece

PRODUCT SPECIFICATION

Length 8 metres

Compatible models LSX II LT



LOGISTIC SPECIFICATION

Packaging dimensions H187 x W230 x D40 mm (7.4 x 9.1 x 1.6 in.)/piece

Gross weight 0.41 kg (0.9 lbs.)/piece

Warranty period 2 years

Finishes Black

Item no. SP4103B0AA

UPC 637203050961

C3 Remote

Remote for LS Wireless Collection



MSRP
€119/piece

PRODUCT SPECIFICATION

Dimensions H185 x W44 x D18 mm
(7.3 x 1.7 x 0.7 in.)/piece

Product weight 0.1kg (0.22 lbs.)/piece

Compatible models Fully compatible:
LS60 Wireless, LS50 Wireless II
Partially compatible:
LSX II (CX button is not supported)
LSX II LT (CX and AUX are not supported)

Batteries 2 x AAA batteries

LOGISTIC SPECIFICATION

Packaging dimensions H220 x W156 x D38 mm (8.7 x 6.1 x 1.5 in.)/piece

Gross weight 0.23 kg (0.5 lbs.)/piece

Warranty period 2 years

Finishes Dark Grey

Item no. SP4113H0AA

UPC 637203051289

Headphones & Accessories



Mu Headphones

Sound by KEF. Design by Ross Lovegrove.



Introducing Mu earphones and headphones, designed in collaboration with Ross Lovegrove. A design that complements KEF's obsession with pure, accurate sound, Mu earphones and headphones are the new chapter in the sound and design journey of KEF and Ross Lovegrove.

Key Features

- Active Noise Cancellation tuned to eliminate external sound while preserving nuance and detail
- Full-range dynamic driver engineered to reveal the smallest details
- Exceptionally stable connections with both iOS and Android devices
- Intuitive touch control of music and calls
- Fast charging
- Ergonomic design for comfort and fit

Mu7


Noise Cancelling Over-ear
Wireless Headphones



MSRP
€399/piece

PRODUCT SPECIFICATION

Speaker drivers	40 mm
Max power output	15 mW
Bluetooth	5.1
Codec	SBC, AAC, aptX, aptX HD
Battery play time	40 hrs (BT + ANC on)
Fast Charging for 15 mins	8 hrs battery play time
Dimensions	H199 x W153 x D89 mm (7.8 x 6 x 3.5 in.)/piece
Product weight	309 g/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H80 x W260 x D230 mm (3.1 x 10.2 x 9.1 in.)/piece	
Gross weight	1 kg (2.2 lbs.)/piece	
Warranty period	2 years	
Finishes	a. Silver Grey	b. Charcoal Grey
Item no.	SP4029GA	SP4029HA
UPC	637203047329	637203047473

Mu3


Noise Cancelling True
Wireless Earphones



MSRP
€230/set

PRODUCT SPECIFICATION

Speaker drivers	8.2 mm
Max power output	5 mW
Bluetooth	5.0
Codec	SBC, AAC
Battery play time	Earbud: 9 hrs (BT + ANC on) Charging case: 15 hrs
Fast Charging for 15 mins	1 hr battery play time
Dimensions	Earbud: H24.5 x W17.5 x D26.3 mm (1 x 0.7 x 1 in.)/piece Charging case: H33.5 x W62 x D52 mm (1.3 x 2.4 x 2 in.)/piece
Product weight	Earbud: 5.8 g/piece Charging case: 46.8 g/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H62 x W162 x D130 mm (2.4 x 6.4 x 5.1 in.)/piece	
Gross weight	0.31 kg (0.7 lbs.)/piece	
Warranty period	2 years	
Finishes	a. Silver Grey	b. Charcoal Grey
Item no.	SP4028GA	SP4028HA
UPC	637203047312	637203047466

Accessories

Mu7 Carrying Case

Protect your headphones in style



MSRP
€n.a./piece

PRODUCT SPECIFICATION

Dimensions H250 x W220 x D65 mm
(9.8 x 8.7 x 2.6 in.)/piece

LOGISTIC SPECIFICATION

Item no. SS4029-01G6

UPC 637203048869

Mu7 Ear Cushions

Designed for comfort



MSRP
n.a./pair

PRODUCT SPECIFICATION


Dimensions H102 x W79 x D26 mm
(4 x 3.1 x 1 in.)/piece

PRODUCT SPECIFICATION

Finishes a. Silver Grey b. Charcoal Grey

Item no. SS4029-01G2 SS4029-01G13

UPC 637203048845 637203048821



Mu7 3.5mm Audio Cord

Wired or wireless, your choice



MSRP
€n.a./piece

PRODUCT SPECIFICATION

Length 1.2m



PRODUCT SPECIFICATION

Finishes a. Silver Grey b. Charcoal Grey

Item no. SS4029-01G15 SS4029-01G14

UPC 637203048852 637203048838

Mu3 Charging Case

Power for the whole day



MSRP
€n.a./piece


PRODUCT SPECIFICATION

Dimensions H33.5 x W62 x D52 mm
(1.3 x 2.4 x 2 in.)/piece

Product weight 46.8g/piece

Battery play time 15 hrs

Battery charging USB-C



LOGISTIC SPECIFICATION

Finishes a. Silver Grey b. Charcoal Grey

Item no. SS4028-01G7 SS4028-01G16

UPC 637203047527 637203047596

Mu3 Ear Tips

Designed for best fit



MSRP
€n.a./set

PRODUCT SPECIFICATION

Package 3 pairs

Dimensions Large: 12.9mm (0.5 in.)
Medium: 12mm (0.47 in.)
Small: 10.7mm (0.42 in.)
Short: 12.1mm (0.48 in.)



LOGISTIC SPECIFICATION

a. Silver Grey				
Size	Short	Small	Medium	Large
Item no.	SS4028-01G6B	SS4028-01G3B	SS4028-01G4B	SS4028-01G5B
UPC	637203047565	637203047534	637203047541	637203047558
b. Charcoal Grey				
Size	Short	Small	Medium	Large
Item no.	SS4028-01G21B	SS4028-01G18B	SS4028-01G19B	SS4028-01G20B
UPC	637203047640	637203047619	637203047626	637203047633



Subwoofers & Accessories



Subwoofers

Immersive power of deep detailed bass



Take home the immersive power of deep detailed bass with unrivalled acoustic accuracy that drops you right into the heart of the action. Over 60 years of innovation in crafting award-winning speakers has made us an authority in sound, and our subwoofer range brings home the visceral experience of modern immersive sound like no other for movies, gaming, music, and streaming.

Reference 8b

Twin 9-inch driver force-cancelling subwoofer



MSRP
€6,000/piece

PRODUCT FEATURES

- Two 500W Class D amplifiers
- KEF's ingenious force-cancelling technology
- Designed, engineered, handcrafted in Maidstone, UK

PRODUCT SPECIFICATION

Design	Force cancelled closed box
Drive units	L.F.: 2 x 225 mm (9 in.)
Frequency response	24 Hz (±3 dB)
Amplifier type	2 x 500 W Class D with switched mode power supply and DSP based control section
Maximum output	110 dB (peak sound pressure level at 1m/50 Hz)
Variable low pass filter	Variable frequency: 40 Hz to 160 Hz Variable slope: 12 dB/oct, 18 dB/oct, 24 dB/oct LFE mode: 350 Hz, 18 dB/oct
Input	RCA phono sockets Analog XLR socket
Power requirements	100 V - 120 V / 220 V - 240 V, 50/60 Hz
Power consumption	1000 W
Dimensions	H398 x W365 x D429 mm (15.7 x 14.4 x 16.8 in./piece)
Product weight	34kg (75 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H598 x W556 x D496 mm (23.5 x 21.9 x 19.5 in./piece)
Gross weight	40.7 kg (89.7 lbs./piece)
Warranty period	2 years electronics, 5 years drivers
Item no.	SP3868BA
UPC	637203042430

KC92

Twin 9-inch driver force-cancelling subwoofer



MSRP
€2,399/piece

PRODUCT FEATURES

- Twin 9-inch force-cancelling driver array
- P-Flex pressure resistant surround design
- Music Integrity Engine® (MIE) – in-house developed DSP to further optimise performance
- iBX Intelligent Bass Extension allows to play louder and remain dynamic at any listening level
- Five room placement settings
- 1000W (2 x 500W) RMS Class D amplification
- Compact sealed cabinet
- Exceptionally versatile controls for easy integration with any loudspeaker and any home environment

Key technologies MIE

PRODUCT SPECIFICATION

Design	Force cancellation
Drive units	L.F.: 2 x 9" drivers
Frequency response	11 Hz - 200 Hz (±3 dB)
Amplifier power	1000W RMS (2 x 500W RMS)
Amplifier class	Built-in Class D
Maximum output	110 dB
Variable low pass filter	40 Hz - 140 Hz, LFE4
Input	RCA phono sockets Speaker level inputs Expansion port for KW1
Power requirements	100 - 240 V, 50/60 Hz
Power consumption	1000 W
Dimensions	H352.4 x W330 x D360.5 mm (13.9 x 13 x 14.2 in./piece)
Product weight	20kg (44.1 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H495 x W460 x D460 mm (19.5 x 18.1 x 18.1 in./piece)
Gross weight	22.6 kg (49.8 lbs./piece)
Warranty period	2 years electronics, 5 years drivers
Finishes	a. White Gloss b. Black Gloss
Item no.	SP4076A0BA SP4076B0BA
UPC	637203050893 637203050824

KC62

The biggest small subwoofer



MSRP
€1,699/piece


PRODUCT FEATURES

- Twin 6.5-inch Uni-Core force cancelling driver array
- P-Flex pressure resistant surround design
- Smart Distortion Control Technology
- Music Integrity Engine with iBX, SmartLimiter and Room Placement settings
- 1000W (2 x 500W) RMS Class D amplification
- Compact sealed aluminium cabinet
- Exceptionally versatile controls for easy integration with any loudspeaker and any home environment

Key technologies Uni-Core®

PRODUCT SPECIFICATION

Design	Uni-Core force cancellation
Drive units	L F: 2 x 6.5 in. drivers
Frequency response	11Hz – 200Hz (±3dB)
Amplifier power	1000W RMS (2 x 500W RMS)
Amplifier class	Built-in Class D
Maximum output	105 dB
Variable low pass filter	40 Hz – 140 Hz, LFE
Low level signal inputs	RCA phono sockets, Speaker level inputs
Power requirements	100 - 240 V, 50/60Hz
Power consumption	1000 W
Dimensions	H246 x W256 x D248 mm (9.68 x 10.07 x 9.76 in./piece)
Product weight	14kg (30.9 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H385 x W400 x D380 mm (15.2 x 15.7 x 15 in./piece)		
Gross weight	15 kg (33 lbs./piece)		
Warranty period	2 years electronics, 5 years drivers		
Finishes	a. Mineral White	b. Carbon Black	c. Titanium Grey
Item no.	SP3949AA	SP3949BA	SP3949HA
UPC	637203217838	637203218033	637203049118

Kube 15 MIE

15-inch front-firing active subwoofer



MSRP
€1,299/piece

PRODUCT FEATURES

- The largest model in the Kube range with the highest output
- Music Integrity Engine® (MIE) – KEF's in-house DSP – optimises the performance of each model
- Three room placement settings
- 300W RMS Class D amplification
- KEF SmartConnect intelligent inputs to automatically detect mono or stereo and adjust the subwoofer volume level accordingly
- Versatile controls for easy integration with any loudspeaker and any home environment
- Sealed for greater accuracy while allowing the Kube to be installed in a cabinet

Key technologies MIE

PRODUCT SPECIFICATION

Design	Powered Subwoofer (Sealed)
Drive units	LF: 1 x 380mm (15in.)
Frequency response	20Hz - 140Hz (±3dB)
Amplifier power	300W RMS
Amplifier class	Class-D
Maximum output	116 dB
Variable low pass filter	40 Hz - 140 Hz, LFE
Inputs	RCA phono sockets, Speaker level inputs, Expansion port for KW1
Power requirements	100-240 V, 50/60 Hz
Power consumption	300 VA
Dimensions	H519 x W500 x D515 mm (20.4 x 19.7 x 20.3 in./piece)
Product weight	27.5 kg (60.6 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H630 x W625 x D605 mm (24.8 x 24.6 x 23.8 in./piece)
Gross weight	34.3 kg (75.6 lbs./piece)
Warranty period	2 years electronics, 5 years drivers
Item no.	SP4102BOBA
UPC	637203050206

Kube 12 MIE

12-inch front-firing active subwoofer



MSRP
€899/piece

PRODUCT FEATURES

- The second large model in the Kube range
- Music Integrity Engine® (MIE) – KEF's in-house DSP – optimises the performance of each model
- Three room placement settings
- 300W RMS Class D amplification
- KEF SmartConnect intelligent inputs to automatically detect mono or stereo and adjust the subwoofer volume level accordingly
- Versatile controls for easy integration with any loudspeaker and any home environment
- Sealed for greater accuracy while allowing the Kube to be installed in a cabinet

Key technologies MIE

PRODUCT SPECIFICATION

Design	Powered Subwoofer (Sealed)
Drive units	L F: 1 x 300mm (12in.)
Frequency response	22Hz - 140Hz (±3dB)
Amplifier power	300W RMS
Amplifier class	Class-D
Maximum output	114 dB
Variable low pass filter	40 Hz - 140 Hz, LFE
Input	RCA phono sockets, Speaker level inputs, Expansion port for KW1
Power requirements	100-240 V, 50/60 Hz
Power consumption	300 VA
Dimensions	H410 x 393 x 410 mm (16.1 x 15.5 x 16.1 in./piece)
Product weight	18.6 kg (41 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H530 x W535 x D480 mm (20.9 x 21.1 x 18.9 in./piece)
Gross weight	21.8 kg (48.1 lbs./piece)
Warranty period	2 years electronics, 5 years drivers
Item no.	SP4075BOBA
UPC	637203050411

Kube 10 MIE

10-inch front-firing active subwoofer



MSRP
€799/piece

PRODUCT FEATURES

- The mid-sized model in the Kube range
- Music Integrity Engine® (MIE) – KEF's in-house DSP – optimises the performance of each model
- Three room placement settings
- 300W RMS Class D amplification
- KEF SmartConnect intelligent inputs to automatically detect mono or stereo and adjust the subwoofer volume level accordingly
- Versatile controls for easy integration with any loudspeaker and any home environment
- Sealed for greater accuracy while allowing the Kube to be installed in a cabinet

Key technologies MIE

PRODUCT SPECIFICATION

Design	Powered Subwoofer (Sealed)
Drive units	LF: 1 x 250mm (10in.)
Frequency response	24Hz - 140Hz (±3dB)
Amplifier power	300W RMS
Amplifier class	Class-D
Maximum output	111 dB
Variable low pass filter	40Hz - 140Hz, LFE
Input	RCA phono sockets, Speaker level inputs, Expansion port for KW1
Power requirements	100-240 V, 50/60 Hz
Power consumption	300 VA
Dimensions	H370 x W353 x D370 mm (14.6 x 13.9 x 14.6 in./piece)
Product weight	15.4 kg (34 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H495 x W495 x D440 mm (19.5 x 19.5 x 17.3 in./piece)
Gross weight	18.3 kg (40.3 lbs./piece)
Warranty period	2 years electronics, 5 years drivers
Item no.	SP4074BOBA
UPC	637203050343

Kube 8 MIE

8-inch front-firing active subwoofer



MSRP
€649/piece

PRODUCT FEATURES

- The most compact model in the Kube range
- Music Integrity Engine® (MIE) – KEF's in-house DSP – optimises the performance of each model
- Three room placement settings
- 300W RMS Class D amplification
- KEF SmartConnect intelligent inputs to automatically detect mono or stereo and adjust the subwoofer volume level accordingly
- Versatile controls for easy integration with any loudspeaker and any home environment
- Sealed for greater accuracy while allowing the Kube to be installed in a cabinet

Key technologies MIE

PRODUCT SPECIFICATION

Design	Powered Subwoofer (Sealed)
Drive units	1 x 200 mm (8 in.)
Frequency response	34 Hz - 140 Hz (-6dB)
Amplifier power	300W RMS
Amplifier class	Class-D
Maximum output	105 dB
Variable low pass filter	40 Hz - 140 Hz, LFE
Input	RCA phono sockets, Speaker level inputs, Expansion port for KW1
Power requirements	100-240 V, 50/60 Hz
Power consumption	300 VA
Dimensions	H293 x W293 x D310 mm (11.5 x 11.5 x 12.2 in./piece)
Product weight	9.4 kg (20.7 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H415 x W410 x D380 mm (16.3 x 16.1 x 15 in.)/piece
Gross weight	11.7 kg (25.8 lbs.)/piece
Warranty period	2 years electronics, 5 years drivers
Item no.	SP4073B0BA
UPC	637203050275

T2 Subwoofer

Slim profile subwoofer



MSRP
€749/piece

PRODUCT FEATURES

- Uniquely slim profile
- 250 Watts Class D amp and 10in. driver

Key technologies MIE

PRODUCT SPECIFICATION

Design	Closed box powered subwoofer
Drive units	1 x 250mm (10in.)
Frequency response	30 Hz - 250 Hz
Amplifier type	250 Watts built-in- Class-D
Maximum output	110 dB
Variable low pass filter	Fixed 250 Hz, 2nd-order
Input	RCA phono sockets
Power requirements	100-240 V ac, 50/60 Hz
Dimensions	H380 x W370 x D177 mm (15.6 x 14.6 x 7.0 in.)/piece
Product weight	13 kg (28.6 lbs.)/piece



LOGISTIC SPECIFICATION

Packaging dimensions	H502 x W490 x D326 mm (19.8 x 19.3 x 12.8 in.)/piece	
Gross weight	12.3 kg (27.1 lbs.)/piece	
Warranty period	2 years electronics, 5 years drivers	
Finishes	a. White	b. Black
Item no.	SP3740ABE	SP3740BBE
UPC	637203210082	637203209413

Accessories

KW1

Wireless Subwoofer Adapter Kit



MSRP
**€229/set,
€129/receiver only**

PRODUCT SPECIFICATION

Radio frequency	5.2GHz and 5.8GHz
Sampling rate	24bit, 48KHz
Latency	<17ms
Link distance	Max. 100 ft (Line of sight)
Frequency response	10 Hz - 20 kHz
Signal-to-noise ratio	>80 dB
Transmitter power Input	5V DC 1A
Audio output level	2 V
Transmitter input level	2 V
Total harmonic distortion	typ.-90 dB
Radio frequency output power	5150-5250MHz<=2 dBm 5725-5850MHz<=7 dBm
Dimensions	Transmitter: H214 x W72 x D79.5mm (0.8 x 2.8 x 3.1 in.)/piece Receiver: H27 x W37 x D72mm (1.1 x 1.5 x 2.8 in.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H80 x W165 x D125 mm (3.1 x 6.5 x 4.9 in.)/set
Gross weight	0.33 kg (0.73 lbs.)/set
Warranty period	2 years
HS code	85255000(00)
Item no.	SP4020BA
UPC	637203046650

KSK92

Subwoofer Stacking Kit



MSRP
€220/set

PRODUCT SPECIFICATION

Dimensions	Frame: H360 x W15 x D10mm (14.2 x 0.6 x 0.4in.)/frame Soft material layer: H310 x W262mm (12.2 x 10.3in.)/piece
Product weight	0.41kg (0.9 lbs.)/pair

LOGISTIC SPECIFICATION

Packaging dimensions	H25 x W404 x D267 mm (1 x 15.9 x 10.5 in.)/pair
Gross weight	0.67 kg (1.5 lbs.)/pair
Warranty period	2 years
HS code	94032080(00)
Item no.	SP4108B0AA
UPC	637203051074

Architectural Speakers & Accessories



Extreme Home Theatre

Bring the Theatre Home



Setting a new standard for architectural speakers, KEF's Extreme Home Theatre pushes the boundaries of technology to bring you best-in-class acoustic performance, impeccable design and easy installation too. Hundreds of performance and quality assurance tests have been undertaken to be THX® Certified Dominus and THX® Certified Ultra, proof of the system's ability to deliver breathtakingly realistic, completely immersive, cinematic sound, just as the director intended.

Key Features

- KEF + THX Testing Lab collaboration: officially certified theatre specifications
- KEF signature Uni-Q technology, offering an open and wide soundstage
- Easy to install with expert finishing and ingenious build quality, ensuring epic performance
- Can be configured vertically or horizontally to suit your needs
- Magnetic grilles included; fabric grilles sold separately for select models

Ci-Reference Series

Ci5160REFM-THX

THX® CERTIFIED DOMINUS

KEF's first THX® Certified Dominus speaker



MSRP
€11,000/piece

PRODUCT SPECIFICATION

Drive Units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5.25 in.) Uni-Q Bass units LF: 4 x 160 mm (6.5 in.)
--------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------

Amplifier requirements	50-500 W
Sensitivity	92dB
Impedance	4Ω

Rough-in frame	RIF5160L
Certification	THX Certified Dominus

Dimensions	H1070 x W230 x D105.7 mm (42.13 x 9.06 x 4.16 in.) /piece
-------------------	--------------------------------------------------------------

Cut-out dimensions	H1052 x W209 mm (41.42 x 8.23 in.)
---------------------------	------------------------------------

Mounting depth from surface	99 mm (3.9 in.)
------------------------------------	-----------------

Product weight	21.7 kg (47.8 lbs.)
-----------------------	---------------------



Designed, Engineered, and handcrafted in Maidstone, UK

LOGISTIC SPECIFICATION

Packaging dimensions	H357 x W1181 x D236 mm (14.06 x 46.50 x 9.29 in.) /piece
Gross weight	24.2 kg (53.4 lbs.) /piece
Warranty period	5 years
Item no	SP4070B0AA
UPC	637203049927

Ci3160REFM-THX

THX® CERTIFIED ULTRA

THX® Certified Ultra Speaker with MAT™



MSRP
€8,000/piece

PRODUCT SPECIFICATION

Drive Units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5.25 in.) Uni-Q Bass units LF: 2 x 160 mm (6.5 in.)
--------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------

Amplifier requirements	50-350W
Sensitivity	89 dB
Impedance	4Ω

Rough-in frame	RIF3160L
Certification	THX Certified Ultra

Dimensions	H680 x W230 x D105.7 mm (26.77 x 9.06 x 4.16 in.) /piece
-------------------	-------------------------------------------------------------

Cut-out dimensions	H660 x W209 mm (25.98 x 8.23 in.)
---------------------------	-----------------------------------

Mounting depth from surface	99 mm (3.9 in.)
------------------------------------	-----------------

Product weight	13.6 kg (29.92 lbs.)
-----------------------	----------------------



Designed, Engineered, and handcrafted in Maidstone, UK

LOGISTIC SPECIFICATION

Packaging dimensions	H233 x W805 x D326 mm (9.17 x 31.69 x 12.83 in.) /piece
Gross weight	15.1 kg (33.3 lbs.) /piece
Warranty period	5 years
Item no	SP4069B0AA
UPC	637203049910

Ci-R Series

Ci5160RLM-THX

THX® CERTIFIED ULTRA

Ultra-high performance architectural speaker with MAT™



MSRP
€2,800/piece

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 160 mm (6.5 in.) Uni-Q Bass units LF: 4 x 160 mm (6.5 in.)
Amplifier requirements	50-350 W
Sensitivity	89 dB
Impedance	4 Ω
Rough-in frame	RIF5160L
Certification	THX Certified Ultra
Dimensions	H1070 x W230 x D105.7 mm (42.13 x 9.06 x 4.16 in.)/piece
Cut-out dimensions	H1052 x W209 mm (41.42 x 8.23 in.)
Mounting depth from surface	99 mm (3.9 in.)
Product weight	18.7 kg (41.1 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H353 x W1178 x D236 mm (13.90 x 46.38 x 9.29 in.)/piece
Gross weight	21.2 kg (46.7 lbs.)/piece
Warranty period	5 years
Item no.	SP4079G0AA
UPC	637203218811

Ci3160RLM-THX

THX® CERTIFIED ULTRA

THX® Certified Ultra Speaker with MAT™



MSRP
€1,800/piece

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 25 mm (1 in.) vented aluminium dome with MAT MF: 125 mm (5.25 in.) Uni-Q Bass units LF: 2 x 160 mm (6.5 in.)
Amplifier requirements	50-350 W
Sensitivity	89 dB
Impedance	4 Ω
Rough-in frame	RIF3160L
Certification	THX Certified Ultra
Dimensions	H680 x W230 x D105.7 mm (26.77 x 9.06 x 4.16 in.)/piece
Cut-out dimensions	H660 x W209 mm (25.98 x 8.23 in.)
Mounting depth from surface	99 mm (3.9 in.)/piece
Product weight	12 kg (26.4 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H322 x W768 x D227 mm (12.68 x 30.24 x 8.94 in.)/piece
Gross weight	13.4 kg (29.5 lbs.)/piece
Warranty period	5 years
Item no.	SP4078G0AA
UPC	637203218804

Ci250RRM-THX

THX® CERTIFIED ULTRA

KEF's First Architectural Speaker with MAT™



MSRP
€1,700/piece

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 19 mm (0.75 in.) vented aluminium dome with MAT MF: 100 mm (4 in.) Uni-Q Bass units LF: 250 mm (10 in.)
Amplifier requirements	50-250 W
Sensitivity	89 dB
Impedance	8 Ω
Certification	THX Certified Ultra, IP64
Dimensions	Ø346 x D175 mm (13.62 x 6.89 in.)/piece
Cut-out dimensions	Ø300 mm (11.81 in.)
Mounting depth from surface	168 mm (6.62 in.)
Product weight	6 kg (13.2 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H422 x W420 x D277 mm (16.61 x 16.54 x 10.91 in.)/piece
Gross weight	8.1 kg (17.9 lbs.)/piece
Warranty period	5 years
Item no.	SP4023AA
UPC	637203218392

Ci200RR-THX

THX® CERTIFIED ULTRA

Features KEF's patented Uni-Q driver array



MSRP
€699/piece

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 38 mm (1.5 in.) Bass units LF: 200 mm (8 in.) Uni-Q
Amplifier requirements	10-190 W
Sensitivity	90 dB
Impedance	4 Ω
Rough-in frame	RIF200R
Rear enclosure	RNC200R
Certification	THX Certified Ultra, IP64
Dimensions	Ø290 x D132.6 mm (11.42 x 5.22 in.)/piece
Cut-out dimensions	Ø238 mm (9.37 in.)
Mounting depth from surface	126.5 mm (4.98 in.)
Product weight	3.6 kg (7.94 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H362 x W357 x D222 mm (14.25 x 14.06 x 8.74 in.)/piece
Gross weight	4.4 kg (9.7 lbs.)/piece
Warranty period	5 years
Item no.	SP3836AA
UPC	637203211430

Ci200RS-THX

THX® CERTIFIED ULTRA

Features KEF's patented Uni-Q driver array



MSRP
€699/piece

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 38 mm (1.5in.) Bass units LF: 200 mm (8in.) Uni-Q
Amplifier requirements	10-190 W
Sensitivity	90 dB
Impedance	4 Ω
Rough-in frame	RIF200S
Rear enclosure	RNC200S
Certification	THX Certified Ultra, IP64
Dimensions	H273 x W273 x D132.6 mm (10.75 x 10.75 x 5.22 in.)/piece
Cut-out dimensions	H240 x W240 mm (9.45 x 9.45 in.)
Mounting depth from surface	127mm (5 in.)
Product weight	3.6 kg (7.94 lbs.) /piece

LOGISTIC SPECIFICATION

Packaging dimensions	H362 x W357 x D222 mm (14.25 x 14.06 x 8.74 in.)/piece
Gross weight	4.5 kg (9.9 lbs.) /piece
Warranty period	5 years
Item no.	SP3927AA
UPC	637203215520

Ci160RR-THX

THX® CERTIFIED ULTRA

THX® Certified Ultra Architectural Speaker



MSRP
€629/piece

PRODUCT SPECIFICATION

Drive units	Uni-Q driver array HF: 25 mm (1 in.) Bass units LF: 165 mm (6.5 in.) Uni-Q
Amplifier requirements	10-150 W
Sensitivity	89 dB
Impedance	4 Ω
Rough-in frame	RIF160R
Rear enclosure	RNC160R
Certification	THX Certified Ultra, IP64
Dimensions	Ø234.6 mm x D115 mm (9.24 in. x 4.53 in.)/piece
Cut-out dimensions	Ø196 mm (7.71 in.)
Mounting depth from surface	110 mm (4.33 in.)
Product weight	2.94 kg (6.48 lbs.) /piece

LOGISTIC SPECIFICATION

Packaging dimensions	H314 x W308 x D187 mm (12.36 x 12.13 x 7.36 in.)/piece
Gross weight	3.5 kg (7.7 lbs.) /piece
Warranty period	5 years
Item no.	SP4021AA
UPC	637203217654

Ci-Q Series

Ci4100QL-THX

THX® CERTIFIED SELECT

Features KEF's patented Uni-Q driver array



MSRP
€500/piece

PRODUCT SPECIFICATION

Drive units	HF: 19 mm (0.75 in.) Uni-Q MF: 100 mm (4 in.) LF: 3 x 100 mm (4 in.)
Amplifier requirements	10 - 150 W
Sensitivity	89 dB
Impedance	4 Ω
Rough-in frame	RIF4100L
Certification	THX Certified Select, IP64
Dimensions	H490 x W128 x D81 mm (19.29 x 5.04 x 3.19 in.)/piece
Cut-out dimensions	H476 x W114 mm (18.74 x 4.49 in.)
Mounting depth from surface	76 mm (3.0 in.)
Product weight	3 kg (6.61 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H191 x W558 x D117 mm (7.52 x 21.97 x 4.61 in.)/piece
Gross weight	3.8 kg (8.4 lbs.) /piece
Warranty period	5 years
Item no.	SP3831AA
UPC	637203211164

Accessories

Cloth Grille

for Ci5160REFM-THX & Ci5160RLM-THX



MSRP
€158/piece

PRODUCT SPECIFICATION

Dimensions	H1044 x W204 x D7 mm (41.1 x 8 x 0.3 in.)/piece
Product weight	0.37 kg (0.8 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H30 x W1060 x D223 mm (1.2 x 41.7 x 8.8 in.)/piece
Gross weight	0.9 kg (2 lbs.)/piece
Warranty period	2 years
Item no.	SP3854BB
UPC	637203212109

Cloth Grille

for Ci3160REFM-THX & Ci3160RLM-THX



MSRP
€116/piece

PRODUCT SPECIFICATION

Dimensions	H654 x W204 x D7 mm (25.7 x 8 x 0.3 in.)/piece
Product weight	0.3 kg (0.7 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H30 x W673 x D223 mm (1.2 x 26.5 x 8.8 in.)/piece
Gross weight	0.6 kg (1.3 lbs.)/piece
Warranty period	2 years
Item no.	SP3852BB
UPC	637203212093

In-Ceiling & In-Wall Speakers

Designed to disappear into your environment



KEF's comprehensive collection of in-ceiling and in-wall architectural speakers offer exceptional performance from models designed to disappear into their environment. Whether you require the class defining abilities or the space saving features, KEF has the perfect speaker for your installation.

Key Features

- Ultra-thin bezel design, magnetic paintable grille
- Weather resistant, IP64 certified
- Fast and easy to install. KEF engineering approved build quality

Ci-Q Series

Ci200QL

Features KEF's patented Uni-Q driver array



MSRP
€471/piece

PRODUCT SPECIFICATION

Drive Units	HF: 25mm (1 in.) LF: 200mm (8 in.) Uni-Q
Amplifier requirements	10-150 W
Sensitivity	90 dB (2.83 V/1 m)
Impedance	8Ω
Rough-in frame	RIF200L
Rear enclosure	RNC200L
Certification	IP64
Dimensions	H369 x W273 x D106 mm (14.53 x 10.75 x 4.27 in./piece)
Cut-out dimensions	H334 x W238 mm (13.15 x 9.37 in.)
Mounting depth from surface	99.8 mm (3.93 in.)
Product weight	2.6 kg (5.77 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H145 x W509 x D355 mm (5.7 x 20 x 14 in./piece)
Gross weight	3.3 kg (7.3 lbs./piece)
Warranty period	5 years
Item no	SP3777AA
UPC	637203208621

Ci160QL

Features KEF's patented Uni-Q driver array



MSRP
€345/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19 mm (0.75 in.) LF: 160 mm (6.5 in.) Uni-Q
Amplifier requirements	10 - 125 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	8Ω
Rough-in frame	RIF160L
Rear enclosure	RNC160L
Certification	IP64
Dimensions	H303 x W223 x D97.5 mm (11.93 x 8.78 x 3.84 in./piece)
Cut-out dimensions	H274 x 194 mm (10.79 x 7.64 in.)
Mounting depth from surface	91 mm (3.58 in.)
Product weight	2.05 kg (4.51 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W382 x D284 mm (5.5 x 15 x 11.2 in./piece)
Gross weight	2.7 kg (6 lbs./piece)
Warranty period	5 years
Item no	SP3775AA
UPC	637203208539

Ci200QS

Features KEF's patented Uni-Q driver array



MSRP
€450/piece

PRODUCT SPECIFICATION

Drive Units	HF: 25 mm (1 in.) Uni-Q LF: 200 mm (8 in.)
Amplifier requirements	10-150 W
Sensitivity	90 dB (2.83V/1m)
Impedance	8 Ω
Rough-in frame	RIF200S
Rear enclosure	RNC200S
Certification	IP64
Dimensions	H273 x W273 x D106 mm (10.75 x 10.75 x 4.17 in./piece)
Cut-out dimensions	H238 x W238 mm (9.37 x 9.37 in.)
Mounting depth from surface	99.8 mm (3.93 in.)
Product weight	2.4 kg (5.3 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H145 x W415 x D355 mm (5.7 x 16.3 x 14 in./piece)
Gross weight	31 kg (6.8 lbs./piece)
Warranty period	5 years
Item no	SP3773AA
UPC	637203208614

Ci160QS

Features KEF's patented Uni-Q driver array



MSRP
€314/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19 mm (0.75 in.) Uni-Q LF: 160 mm (6.5 in.)
Amplifier requirements	10-125 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF160S
Rear enclosure	RNC160S
Certification	IP64
Dimensions	H223 x W223 x D97 mm (8.78 x 8.78 x 3.82 in./piece)
Cut-out dimensions	194 x 194 mm (7.64 x 7.64 in.)
Mounting depth from surface	91 mm (3.58 in.)
Product weight	1.88 kg (4.14 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W302 x D284 mm (5.5 x 11.9 x 11.2 in./piece)
Gross weight	2.4 kg (5.3 lbs./piece)
Warranty period	5 years
Item no	SP3771AA
UPC	637203208515

Ci130QS

Features KEF's patented Uni-Q driver array



MSRP
€261/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19 mm (0.75 in.) LF: 130 mm (5.25 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	87 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF130S
Rear enclosure	RNC130S
Certification	IP64
Dimensions	H184 x W184 x D84 mm (7.24 x 7.24 x 3.26 in./piece)
Cut-out dimensions	H158 x W158 mm (6.22 x 6.22 in.)
Mounting depth from surface	77.9 mm (3.07 in.)
Product weight	1.4 kg (3.1 lbs.) /piece

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W275 x D255 mm (5.5 x 10.8 x 10 in./piece)
Gross weight	1.8 kg (4 lbs./piece)
Warranty period	5 years
Item no	SP3768AA
UPC	637203208706

Ci200QR

Thin bezel and narrow rim allow for flawless integration



MSRP
€450/piece

PRODUCT SPECIFICATION

Drive Units	HF: 25 mm (1 in.) LF: 200 mm (8.0 in.) Uni-Q
Amplifier requirements	10-150 W
Sensitivity	90 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF200R
Rear enclosure	RNC200R
Certification	IP64
Dimensions	Ø289.6 x D109.8 mm (11.4 x 4.33 in.) /piece
Cut-out dimensions	Ø240 mm (9.45 in.)
Mounting depth from surface	103.3 mm (4.07 in.)
Product weight	2.4 kg (5.28 lbs.) /piece

LOGISTIC SPECIFICATION

Packaging dimensions	H145 x W353 x D353 mm (5.7 x 13.9 x 13.9 in./piece)
Gross weight	3.2 kg (7.1 lbs./piece)
Warranty period	5 years
Item no	SP3734AA
UPC	637203207488

Ci160QR

Features KEF's patented Uni-Q driver array



MSRP
€314/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19mm (0.75 in.) LF: 160mm (6.5 in.) Uni-Q
Amplifier requirements	10-125 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF160R
Rear enclosure	RNC160R
Certification	IP64
Dimensions	Ø234.6 x D98 mm (9.24 x 3.86 in./piece)
Cut-out dimensions	Ø196 mm (7.71 in.)
Mounting depth from surface	91 mm (3.58 in.)
Product weight	2.05 kg (4.51 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W285 x D285 mm (5.5 x 11.2 x 11.2 in./piece)
Gross weight	2.3 kg (5.1 lbs./piece)
Warranty period	5 years
Item no	SP3733AA
UPC	637203207204

Ci130QR

Features KEF's patented Uni-Q driver array



MSRP
€261/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19 mm (0.75 in.) LF: 130 mm (5.25 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	87 dB (2.83V/1m)
Impedance	8 Ω
Rough-in frame	RIF130R
Rear enclosure	RNC130R
Certification	IP64
Dimensions	Ø193.4 x D83mm (7.61 x 3.28 in./piece)
Cut-out dimensions	158 mm (6.22 in.)
Mounting depth from surface	77.8 mm (3.06 in.)
Product weight	1.35 kg (2.97 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H137 x W259 x D258 mm (5.4 x 10.2 x 10.2 in./piece)
Gross weight	1.8 kg (4 lbs./piece)
Warranty period	5 years
Item no	SP3732AA
UPC	637203207464

Ci-C Series

Ci160.2CL

Features KEF's patented Uni-Q driver array



MSRP
€261/piece

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 160 mm (6.5 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF160L
Rear enclosure	RNC160L
Certification	IP64
Dimensions	H303 x W223 x D 68.7 mm (11.93 x 8.78 x 3.49 in./piece)
Cut-out dimensions	H274 x W194 mm (10.79 x 7.64 in.)
Mounting depth from surface	84.5 mm (3.33 in.)
Product weight	1.6 kg (3.5 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W382 x D284 mm (5.5 x 15 x 11.2 in./piece)
Gross weight	2.2 kg (4.9 lbs./piece)
Warranty period	5 years
Item no	SP3933AA
UPC	637203215407

Ci160.2CS

Features KEF's patented Uni-Q driver array



MSRP
€240/piece

PRODUCT SPECIFICATION

Drive Units	HF: 16mm (0.6 in.) LF: 160mm (6.5 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF160S
Rear enclosure	RNC160S
Certification	IP64
Dimensions	H223 x W223 x D68.7 mm (8.78 x 8.78 x 3.49 in./piece)
Cut-out dimensions	H194 x W194mm (7.64 x 7.64 in.)
Mounting depth from surface	84.5 mm (3.33 in.)
Product weight	1.5 kg (3.3 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W302 x D284 mm (5.5 x 11.9 x 11.2 in./piece)
Gross weight	2 kg (4.4 lbs./piece)
Warranty period	5 years
Item no	SP3934AA
UPC	637203215421

Ci130.2CS

Features KEF's patented Uni-Q driver array



MSRP
€209/piece

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 130 mm (5.25 in.) Uni-Q
Amplifier requirements	10-80 W
Sensitivity	87 dB (2.83 V/1m)
Impedance	8 Ω
Rough-in frame	RIF130S
Rear enclosure	RNC130S
Certification	IP64
Dimensions	H184 x W184 x D81 mm (7.24 x 7.24 x 3.19 in./piece)
Cut-out dimensions	H158 x W158 mm (6.22 x 6.22 in.)
Mounting depth from surface	77.1 mm (3.03 in.)
Product weight	1.2 kg (2.7 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W275 x D255 mm (5.5 x 10.8 x 10 in./piece)
Gross weight	1.6 kg (3.5 lbs.)/piece
Warranty period	5 years
Item no	SP3935AA
UPC	637203215445

Ci200.2CR

Features KEF's patented Uni-Q driver array



MSRP
€345/piece

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 200 mm (8 in.) Uni-Q
Amplifier requirements	10-125 W
Sensitivity	90 dB (2.83 V/1m)
Impedance	8 Ω
Rough-in frame	RIF200R
Rear enclosure	RNC200R
Certification	IP64
Dimensions	Ø289.6 mm x D103.3 mm (11.4 x 4.07 in./piece)
Cut-out dimensions	Ø240 mm (9.45 in.)
Mounting depth from surface	97.2 mm (3.83 in.)
Product weight	1.7 kg (3.7 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H145 x W353 x D353 mm (5.7 x 13.9 x 13.9 in./piece)
Gross weight	2.4 kg (5.3 lbs.)/piece
Warranty period	5 years
Item no	SP3936AA
UPC	637203215469

Ci160.2CR

Features KEF's patented Uni-Q driver array



MSRP
€240/piece

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 160 mm (6.5 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	89 dB (2.83 V/1m)
Impedance	8 Ω
Rough-in frame	RIF160R
Rear enclosure	RNC160R
Certification	IP64
Dimensions	Ø234.6 mm x D88.7 mm (9.24 x 3.49 in./piece)
Cut-out dimensions	Ø196 mm (7.71 in.)
Mounting depth from surface	84.5 mm (3.33 in.)
Product weight	1.4 kg (3.1 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W284 x D284 mm (5.5 x 11.2 x 11.2 in./piece)
Gross weight	1.9 kg (4.2 lbs.)/piece
Warranty period	5 years
Item no	SP3937AA
UPC	637203215483

Ci130.2CR

Features KEF's patented Uni-Q driver array



MSRP
€209/piece

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 130 mm (5.25 in.) Uni-Q
Amplifier requirements	10-80 W
Sensitivity	87 dB (2.83 V/1m)
Impedance	8 Ω
Rough-in frame	RIF130R
Rear enclosure	RNC130R
Certification	IP64
Dimensions	Ø193.4 mm x D82.3 mm (7.61 x 3.24 in./piece)
Cut-out dimensions	Ø158 mm (6.22 in.)
Mounting depth from surface	77.7 mm (3.06 in.)
Product weight	1.3 kg (2.8 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H137 x W255 x D255 mm (5.4 x 10 x 10 in./piece)
Gross weight	1.8 kg (4 lbs.)/piece
Warranty period	5 years
Item no	SP3938AA
UPC	637203215506

Ci-E Series

Ci160ES

Unprecedented value and performance



MSRP
€334/pair

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 160 mm (6.5 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF160S
Rear enclosure	RNC160S
Certification	IP64
Dimensions	H223 x W223 x D88.7 mm (8.78 x 8.78 x 3.49 in.)/piece
Cut-out dimensions	H194 x W194 mm (7.64 x 7.64 in.)
Mounting depth from surface	85.2 mm (3.35 in.)
Product weight	1.4 kg (3.1 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H286 x W281 x D276 mm (11.3 x 11.1 x 10.9 in.)/pair
Gross weight	3.6 kg (7.9 lbs.)/pair
Warranty period	5 years
Item no	SP4038AA
UPC	637203218149

Ci200ER

Heard but not seen, with unprecedented value and performance.



MSRP
€418/pair

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 200 mm (8 in.) Uni-Q
Amplifier requirements	10-125 W
Sensitivity	90 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF200R
Rear enclosure	RNC200R
Certification	IP64
Dimensions	Ø289.6 mm x D103.3 mm (11.4 x 4.07 in.)/piece
Cut-out dimensions	Ø240 mm (9.45 in.)
Mounting depth from surface	97.2 mm (3.83 in.)
Product weight	1.6 kg (3.6 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H343 x W319 x D334 mm (13.5 x 12.6 x 13.1 in.)/pair
Gross weight	3.9 kg (8.6 lbs.)/pair
Warranty period	5 years
Item no	SP3910AA
UPC	637203213472

Ci160ER

Unprecedented value and performance



MSRP
€334/pair

PRODUCT SPECIFICATION

Drive Units	HF: 16mm (0.6 in.) LF: 160mm (6.5 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF160R
Rear enclosure	RNC160R
Certification	IP64
Dimensions	Ø234.6 x D88.7 mm (9.24 x 3.49 in.)/piece
Cut-out dimensions	Ø196 mm (7.71 in.)
Mounting depth from surface	85.2 mm (3.35 in.)
Product weight	1.4 kg (3.1 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H286 x W281 x D276 mm (11.3 x 11.1 x 10.9 in.)/pair
Gross weight	3.3 kg (7.3 lbs.)/pair
Warranty period	5 years
Item no	SP3909AA
UPC	637203213458

Ci130ER

Unprecedented value and performance



MSRP
€270/pair

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 130 mm (5.25 in.) Uni-Q
Amplifier requirements	10-80 W
Sensitivity	90 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RIF130R
Rear enclosure	RNC130R
Certification	IP64
Dimensions	Ø193.4 mm x D81 mm (7.61 x 3.19 in.)/piece
Cut-out dimensions	Ø158 mm (6.22 in.)
Mounting depth from surface	77.5 mm (3.05 in.)
Product weight	1.2 kg (2.7 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H248 x W261 x D241 mm (9.8 x 10.3 x 9.5 in.)/pair
Gross weight	2.7 kg (6 lbs.)/pair
Warranty period	5 years
Item no	SP3908AA
UPC	637203213434

Special Applications



With a Flush Mount, an Extremely Low Profile, Dual Stereo and Soundlight speakers, KEF's architectural speakers are designed to cater to even the most specific needs, and a wide variety of installation setups. The discreet design only serves to enhance its extremely powerful performance.

Key Features

- Ultra-thin bezel design, magnetic paintable grille
- Fast and easy to install
KEF engineering approved build quality

Soundlight

Ci100QS

Soundlight speaker



MSRP
€209/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19mm (0.75in.) LF: 100mm (4in.) Uni-Q
Amplifier requirements	10-50 W
Sensitivity	88 dB (2.83 V/1m)
Impedance	4 Ω
Rough-in frame	RIF100S
Rear enclosure	RNC100S
Certification	IP64
Dimensions	H127 x W127 x H76 mm (5.0 x 5.0 x 2.99 in./piece)
Cut-out dimensions	H112x W112 mm (4.41 x 4.41 in.)
Mounting depth from surface	72 mm (2.83 in.)
Product weight	0.67kg (1.48 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H114 x W173 x D173 mm (4.5 x 6.8 x 6.8 in./piece)
Gross weight	0.9 kg (2 lbs./piece)
Warranty period	5 years
Item no	SP3765AA
UPC	637203208966

Ci100.2QR

Soundlight speaker



MSRP
€209/piece

PRODUCT SPECIFICATION

Drive Units	HF: 16 mm (0.6 in.) LF: 75 mm (3 in.) Uni-Q
Amplifier requirements	10-50 W
Sensitivity	83 dB (2.83 V/1m)
Impedance	4 Ω
Rough-in frame	RIF100R
Rear enclosure	RNC100R
Certification	IP64
Dimensions	Ø136 mm x D57 mm (5.4 x 2.2 in./piece)
Cut-out dimensions	Ø118 mm (4.6 in.)
Mounting depth from surface	103 mm (4.1 in.)
Product weight	0.65 kg (1.44 lbs./piece)

LOGISTIC SPECIFICATION

Packaging dimensions	H155 x W216 x D216 mm (6.1 x 8.5 x 8.5 in./piece)
Gross weight	0.9 kg (2 lbs./piece)
Warranty period	5 years
Item no	SP3928AA
UPC	637203215377

Flush Mount

Ci130QSfl

Flush Mount Speaker



MSRP
€450/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19mm (0.75 in.) LF: 130mm (5.25 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	87 dB (2.83 V/1 m)
Impedance	8 Ω
Certification	IP64
Dimensions	H200.5 x W200.5 x D103.6 mm (7.9 x 7.9 x 4.08 in.)/piece
Cut-out dimensions	H158 x W158 mm (6.22 x 6.22 in.)
Mounting depth from surface	101 mm (3.98 in.)
Product weight	1.6 kg (3.53 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H157 x W252 x D250 mm (6.2 x 9.9 x 9.8 in.)/piece
Gross weight	1.9 kg (4.2 lbs.)/piece
Warranty period	5 years
Item no	SP4019AA
UPC	637203217647

Ci130QRfl

Flush Mount Speaker



MSRP
€450/piece

PRODUCT SPECIFICATION

Drive Units	HF: 19 mm (0.75 in.) LF: 130 mm (5.25 in.) Uni-Q
Amplifier requirements	10-100 W
Sensitivity	87 dB (2.83 V/1 m)
Impedance	8 Ω
Certification	IP64
Dimensions	Ø200.6 mm x D104.6 mm (7.9 x 4.12 in.)/piece
Cut-out dimensions	Ø158 mm (6.22 in.)
Mounting depth from surface	101 mm (3.98 in.)
Product weight	1.45 kg (3.19 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H157 x W252 x D250 mm (6.2 x 9.9 x 9.8 in.)/piece
Gross weight	1.8 kg (4 lbs.)/piece
Warranty period	5 years
Item no	SP4012AA
UPC	637203217630

Dual Stereo

Ci160CSds

Dual stereo speaker



MSRP
€293/piece

PRODUCT SPECIFICATION

Drive Units	HF: 2 x 19mm (0.75 in.) LF: 160mm (6.5 in.) Dual voice coil
Amplifier requirements	10-80W
Sensitivity	91 dB (2.83V/1m)
Impedance	8Ω
Rough-in frame	RiF160S
Rear enclosure	RNC160S
Certification	IP64
Dimensions	H223 x W223 x D90.5mm (8.78 x 8.78 x 3.56 in.)/piece
Cut-out dimensions	H194 x W194 mm (7.64 x 7.64 in.)
Mounting depth from surface	84.5 mm (3.33 in.)
Product weight	1.8 kg (4 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W302 x D284 mm (5.5 x 11.9 x 11.2 in.)/piece
Gross weight	2.3 kg (5.1 lbs.)/piece
Warranty period	5 years
Item no	SP3769AA
UPC	637203208768

Ci160CRds

Dual stereo speaker



MSRP
€n.a./piece

PRODUCT SPECIFICATION

Drive Units	HF: 2 x 19mm (0.75 in.) LF: 160mm (6.5 in.) Dual voice coil
Amplifier requirements	10-80W
Sensitivity	91 dB (2.83 V/1 m)
Impedance	8 Ω
Rough-in frame	RiF160R
Rear enclosure	RNC160R
Certification	IP64
Dimensions	Ø234.6 mm x D93 mm (9.24 x 3.66 in.)/piece
Cut-out dimensions	Ø196 mm (7.71 in.)
Mounting depth from surface	86 mm (3.36 in.)
Product weight	1.80 kg (4.0 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H139 x W285 x D284 mm (5.5 x 11.2 x 11.2 in.)/piece
Gross weight	2.2 kg (4.9 lbs.)/piece
Warranty period	5 years
Item no	SP3687AA
UPC	637203207181

Extremely Low Profile

Ci160TS

Extremely Low Profile speaker



MSRP
€345/piece

PRODUCT SPECIFICATION

Drive Units	HF: 25 mm (1 in.) LF: 115 mm (4.5 in.) Dual layer
Amplifier requirements	10-100W
Sensitivity	87 dB (2.83V/1m)
Impedance	8Ω
Rough-in frame	RIF160S
Certification	IP64
Dimensions	H222.8 x W222.8 x D41mm (8.77 x 8.77 x 1.61 in.)/piece
Cut-out dimensions	H194 x W194 mm (7.64 x 7.64 in.)
Mounting depth from surface	36mm (1.42 in.)
Product weight	1.05kg (2.31lbs)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H84 x W284 x D284 mm (3.3 x 11.2 x 11.2 in.)/piece
Gross weight	1.6 kg (3.5 lbs.)/piece
Warranty period	5 years
Item no	SP3884AA
UPC	637203212420

Ci160TR

Extremely Low Profile speaker



MSRP
€345/piece

PRODUCT SPECIFICATION

Drive Units	HF: 25mm (1 in.) aluminium HF LF: 115mm (4.5 in.) dual layer MF
Amplifier requirements	10-100W
Sensitivity	87dB (2.83V/1m)
Impedance	8Ω
Rough-in frame	RIF160R
Certification	IP64
Dimensions	Ø234.6 mm x D40 mm (9.24 x 1.57 in.)/piece
Cut-out dimensions	Ø196mm (7.7in.)
Mounting depth from surface	36mm (1.42 in.)
Product weight	1 kg (2.2 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H77 x W283 x D283 mm (3 x 11.1 x 11.1 in.)/piece
Gross weight	1.5 kg (3.3 lbs.)/piece
Warranty period	5 years
Item no	SP3830AA
UPC	637203210983

Installed subwoofers



KEF's installed subwoofers offer incredible sonic performance whilst remaining visually discreet, and they are all engineered to partner any of KEF's architectural speaker ranges. Plus, when powered by KEF's DSP-driven KASA500 install audio system amplifier, the Ci316ORLb-THX, Ci250RRb-THX and Ci200QSb-THX subwoofers achieve the intense bass performance levels required for THX Certified Select and THX Certified Ultra (dependent on configuration).

Ci316ORLb-THX

THX Certified Ultra in-wall subwoofer

THX CERTIFIED ULTRA

THX CERTIFIED SELECT



MSRP
€1,249/piece

PRODUCT SPECIFICATION

Series	Ci-R Series
Drive units	LF: 3 x 160 mm (6.5 in.)
Amplifier requirements	KEF KASA500 Units required for THX Ultra (Subwoofer KASA500): 4 2 Units required for THX Select (Subwoofer KASA500): 2 1
Sensitivity	92 dB (2.83 V/1 m)
Impedance	4Ω
Rough-in frame	RIF3160L
Certification	THX Certified Ultra, THX Certified Select
Dimensions	H680 x W230 x D96 mm (26.77 x 9.06 x 3.78 in.)/piece
Cut-out dimensions	H660 x W209 mm (25.98 x 8.23 in.)
Mounting depth from surface	88.5 mm (3.84 in.)
Product weight	10.9 kg (24.03 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H322 x W768 x D227 mm (14.25 x 30.24 x 8.94 in.) /piece
Gross weight	12.3 kg (27.12 lbs.)/piece
Warranty period	5 years
Item no.	SP3835AA
UPC	637203211867

Ci250RRb-THX

The extreme architectural subwoofer

THX CERTIFIED ULTRA

THX CERTIFIED SELECT



MSRP
€1,250/piece

PRODUCT SPECIFICATION

Series	Ci-R Series
Drive units	LF: 250 mm (10 in.)
Amplifier requirements	KEF KASA500 Units required for THX Ultra (Subwoofer KASA500): 4 1 Units required for THX Select (Subwoofer KASA500): 2 1
Sensitivity	109 dB (2.83 V/1 m)
Impedance	4Ω
Certification	THX Certified Ultra, THX Certified Select IP64
Dimensions	Ø: 346 mm x D153 mm (13.62 x 6.0 in.)/piece
Cut-out dimensions	Ø: 300 mm (11.81 in.)
Mounting depth from surface	147 mm (5.8 in.)
Product weight	5.6 kg (12.3 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H422 x W420 x D247 mm (16.6 x 16.5 x 9.7 in.)/piece
Gross weight	6.4 kg (14.1 lbs.)/piece
Warranty period	5 years
Item no.	SP4040AA
UPC	637203218408

Ci200Qsb-THX

THX Certified Ultra 200mm subwoofer

THX CERTIFIED ULTRA

THX CERTIFIED SELECT



MSRP
€840/pair

PRODUCT SPECIFICATION

Series	Ci-Q Series
Drive units	LF: 200 mm (8 in.)
Amplifier requirements	KEF KASA500 Units required for THX Ultra (Subwoofer KASA500): 4 2 Units required for THX Select (Subwoofer KASA500): 2 1
Sensitivity	85 dB - Passive Mode (Crossover "ON")
Impedance	6 Ω
Rough-in frame	RIF200S
Certification	THX Certified Ultra, THX Certified Select IP64
Dimensions	H273 x W273 x D106 mm (10.75 x 10.75 x 4.17 in.)/piece
Cut-out dimensions	H238 x W238 mm (9.37 x 9.37 in.)
Mounting depth from surface	101.6 mm (4 in.)
Product weight	3.3 kg (7.28 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H369 x W363 x D340 mm (14.5 x 14.3 x 13.4 in.)/piece
Gross weight	7.6 kg (16.8 lbs.)/piece
Warranty period	5 years
Mode	Passive mode Active mode
Item no.	SP3894AA
UPC	637203212413

Ci200TRb

The extreme architectural subwoofer



MSRP
€524/piece

PRODUCT SPECIFICATION

Series	Ci-T Series
Drive units	LF: 200 mm (8 in.)
Amplifier requirements	KEF KASA500 Units required for THX Ultra (Subwoofer KASA500): 4 1 Units required for THX Select (Subwoofer KASA500): 2 1
Sensitivity	87 dB (2.83 V/1 m)
Impedance	4 Ω
Rough-in frame	RIF200R
Certification	IP64
Dimensions	Ø: 290 mm x D63 mm (11.42 x 2.48 in.)/piece
Cut-out dimensions	240 mm (9.45 in.)
Mounting depth from surface	26 mm (1.03 in.)
Product weight	1.7 kg (3.75 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H96 x W356 x D354 mm (3.8 x 14 x 13.9 in.)/piece
Gross weight	2.4 kg (5.3 lbs.)/piece
Warranty period	5 years
Mode	Passive mode Active mode
Item no.	SP3845AA
UPC	637203212406

Accessories

KASA500

powerful Class-D Dual 250WPC amplifier



MSRP
€1199/piece

PRODUCT SPECIFICATION

Inputs	Selectable stereo RCA line level, or mono LFE RCA level; Stereo speaker level
Outputs	2 x 250 W 4 Ω Bridge 1 x 500 W 8 Ω (<1% THD)
Dimensions	H88 x W432 x D304 mm (3.5 x 17 x 12 in.)/piece
Product weight	4 kg (9 lbs.)/piece

LOGISTIC SPECIFICATION

Packaging dimensions	H198 x W496 x D390 mm (7.8 x 19.5 x 15.4 in.)/piece
Gross weight	5.3 kg (11.7 lbs.)/piece
Warranty period	5 years
Item no.	SP3838BB
UPC	637203211133

Outdoor



On the patio, by the pool, or on a yacht, the KEF Ventura Series outdoor speakers let you enjoy music without compromise. Engineered to IP65 standards, these rugged, hard-wearing speakers can withstand even the most extreme weather conditions.

Key Features

- All metal design, powder coated to extremes to last and last
- High-quality sound that meets KEF engineering expectations
- Weather resistant, IP65 certified, salt spray tested for over 1200 hours
- All mounting hardware is included
- Rugged, hard-wearing speakers can withstand even most extreme weather

Ventura 6

Outdoor Speakers



MSRP
€576/pair

PRODUCT SPECIFICATION

Drive units	HF: 25 mm (1 in.) LF: 160 mm (6.5 in.)
Amplifier requirements	10-125 W
Sensitivity	90 dB (2.83 V/1 m)
Impedance	6 Ω
Operating temperature range	-40° C to 70° C (-40° F to 158° F)
Certification	IP65
Dimensions	H300 x W226 x D219 mm (11.8 x 9 x 8.6 in./piece)
Product weight	3.8 kg (8.4 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H357 x W596 x D288 mm (14.1 x 23.5 x 11.3 in./piece)	
Gross weight	8 kg (17.6 lbs./piece)	
Warranty period	5 years	
Finishes	a. Black	b. White
Item no.	SP3676BA	SP3676AA
UPC	637203043109	637203028809

Ventura 5

Outdoor Speakers



MSRP
€472/pair

PRODUCT SPECIFICATION

Drive units	HF: 25 mm (1 in.) LF: 130 mm (5.25 in.)
Amplifier requirements	10-100 W
Sensitivity	89 dB (2.83 V/1 m)
Impedance	6 Ω
Operating temperature range	-40° C to 70° C (-40° F to 158° F)
Certification	IP65
Dimensions	H262 x W197 x D189 mm (10.3 x 7.75 x 7.4 in./piece)
Product weight	2.85 kg (6.28 lbs./piece)



LOGISTIC SPECIFICATION

Packaging dimensions	H330 x W541 x D257 mm (13 x 21.3 x 10.1 in./piece)	
Gross weight	6.3 kg (13.9 lbs./piece)	
Warranty period	5 years	
Finishes	a. Black	b. White
Item no.	SP3675BA	SP3675AA
UPC	637203031090	637203028793

Accessories

Steel Rough-in Frames

For in-wall and in-ceiling speakers



MSRP		
	RIF100S	€40/pair
	RIF100R	€40/pair
	RIF130S	€40/pair
	RIF130R	€40/pair
	RIF160L	€40/pair
	RIF160S	€40/pair
	RIF160R	€40/pair
	RIF200L	€40/pair
	RIF200S	€40/pair
	RIF200R	€40/pair
	RIF4100L	€110/pair
	RIF3160L	€178/pair
	RIF5160L	€358/pair

PRODUCT SPECIFICATION

Dimensions		
	RIF100S & RIF100R	H149 x W590 mm (5.9 x 23.2 in.)/piece
	RIF130S & RIF130R	H187 x W590 mm (7.4 x 23.2 in.)/piece
	RIF130S & RIF130R	H187 x W590 mm (7.4 x 23.2 in.)/piece
	RIF160L	H320 x W590 mm (13 x 23.2 in.)/piece
	RIF160S & RIF160R	H240 x W590 mm (9.5 x 23.2 in.)/piece
	RIF200L	H386 x W590 mm (15.2 x 23.2 in.)/piece
	RIF200S & RIF200R	H280 x W590 mm (11 x 23.2 in.)/piece
	RIF4100L	H530 x W571 mm (20.9 x 22.5 in.)/piece
	RIF3160L	H712 x W590 mm (28 x 23.2 in.)/piece
	RIF5160L	H1102 x W590 mm (43.4 x 23.2 in.)/piece

Steel Rear Enclosures

For in-wall and in-ceiling speakers



MSRP		
	RNC100R	€90/piece
	RNC130R	€90/piece
	RNC160R	€120/piece
	RNC200R	€130/piece
	RNC130S	€90/piece
	RNC160S	€120/piece
	RNC200S	€130/piece
	RNC100S	€90/piece
	RNC200L	€130/piece
	RNC160L	€120/piece
	Ci520 CAN SGL	€n.a./piece

PRODUCT SPECIFICATION

Dimensions		
	RNC100R	H590 x W390 x D95 mm (23.2 x 15.4 x 3.7 in.)/piece
	RNC130R	H590 x W390 x D95 mm (23.2 x 15.4 x 3.7 in.)/piece
	RNC160R	H590 x W650 x D100 mm(23.2 x 26 x 3.9 in.)/piece
	RNC200R	H590 x W650 x D100 mm(23.2 x 26 x 3.9 in.)/piece
	RNC130S	H590 x W390 x D95 mm (23.2 x 15.4 x 3.7 in.)/piece
	RNC160S	H590 x W650 x D100 mm(23.2 x 26 x 3.9 in.)/piece
	RNC200S	H590 x W650 x D100 mm(23.2 x 26 x 3.9 in.)/piece
	RNC100S	H590 x W390 x D95 mm (23.2 x 15.4 x 3.7 in.)/piece
	RNC200L	H590 x W650 x D100 mm(23.2 x 26 x 3.9 in.)/piece
	RNC160L	H590 x W650 x D100 mm(23.2 x 26 x 3.9 in.)/piece

Listen and believe

Explore more



GP Acoustics (UK) Ltd

Address: Eccleston Road, Tovil, Maidstone, Kent, ME15 6QP

Telephone: +44(0)1622 672261

Email: sales.uk@kef.com

Online: uk.kef.com

NB Some of the information in this price list may not have been updated due to product changes which may have occurred since it was printed/published. The manufacturer reserves the right to make changes at any time, without notice, to prices, colour, materials, specifications and models.

